




AD-A259 486 GE

Form Approved
OMB No. 0704-0188Public reporting burden
gathering and maintain
collection of information
Davis Highway, Suite 1sponse, including the time for reviewing instructions, searching existing data sources,
ormation. Send comments regarding this burden estimate or any other aspect of this
quarters Services, Directorate for Information Operations and Reports, 1215 Jefferson
dget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE December 1991		3. REPORT TYPE AND DATES COVERED	
4. TITLE AND SUBTITLE Performance of the Monopole Antenna Element for the 96- Element Receiving Array of the High-Frequency, High- Resolution Experimental Site: Volume 2 - Appendices				5. FUNDING NUMBERS 	
6. AUTHOR(S) R. L. Lagace					
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) The MITRE Corporation 202 Burlington Road Bedford, MA 01730-1420				8. PERFORMING ORGANIZATION REPORT NUMBER MTR 11291 Volume 2	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) same as above				10. SPONSORING/MONITORING AGENCY REPORT NUMBER same as above	
11. SUPPLEMENTARY NOTES				92-33088  15118	
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution unlimited				12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) See attached 					
14. SUBJECT TERMS Antenna Element, Numerical Electromagnetics Code-Ground Screen (NEC-GS)				15. NUMBER OF PAGES 138	
				16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT Unlimited		

MTR11291
Volume 2
December 1991

Contract Sponsor MSR
Contract No. N/A
Project No. 91030
Dept. D085

Accession For	
NTIS CRA&I	<input checked="" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution /	
Availability Codes	
Dist	Avail and/or Special
A-1	

Bedford, Massachusetts

ALL INFORMATION CONTAINED HEREIN IS UNCLASSIFIED

Department Approval:

J. Daniel Mayhew

MITRE Project Approval:

Edward A. Polo

ABSTRACT

The theoretical performance of the antenna element for the 96-element receiving array of MITRE's High-Frequency, High-Resolution Experimental Site is analyzed. The antenna element consists of a monopole tower with a buried radial-wire ground screen of modest diameter. Each element is connected by a long buried coaxial cable to an associated receiver in one of three electronics shelters within the array. The analysis forms the basis for selecting the final design configuration of the monopole antenna element, its associated ground screen, and the buried feed cable. System internal noise figure and antenna directivity serve as the principal measures of performance. The contributions of antenna efficiency, cable mismatch loss, cable attenuation loss, and receiver noise figure to system internal noise figure are treated.

The monopole antenna element and an alternative dipole antenna element are modeled and analyzed using the Numerical Electromagnetics Code-Ground Screen (NEC-GS) version of the NEC Method-of-Moments software. NEC-GS, which is particularly well-suited for modeling azimuthally symmetric structures, is used to calculate the antenna input impedance, efficiency, and power gain pattern. The antenna efficiency, cable mismatch loss, and antenna directivity pattern are determined as a function of frequency, earth electrical properties, and antenna element/ground-screen geometry. Asymmetric radiation pattern effects caused by a long, buried or unburied, coaxial feed cable, and by a nearby electronics shelter, are also evaluated. This is accomplished by using NEC software versions NEC-3I and NEC-3 to model the monopole with ground screen in the presence of a jacketed feed cable and a shelter, respectively. Included are brief descriptions of NEC-GS, NEC-3, and NEC-3I versions of NEC, and some associated modeling constraints.

ACKNOWLEDGMENTS

J. D. R. Kramer and M. M. Weiner provided constructive observations and suggestions during the course of the work and review of this report.

M. K. Eggimann and L. Giandomenico executed a large number of NEC computer runs during the course of this work.

S. Zamosciany generated the performance plots from Numerical Electromagnetic Code (NEC) computer output files.

M. H. Weeden and C. S. E. Sherman prepared the balance of the graphics and tables.

J. K. Viveiros prepared the typed manuscript.

Figures 5 and 6; and figures 7, 8, and 36 are modified versions of figures from two MITRE reports MTR-9221, March 1984 and MTR-11278, September 1991, respectively, by M. M. Weiner.

TABLE OF CONTENTS

SECTION	PAGE
A1 Overview	1
A2 5.4 Meter Monopole Configuration Results	3
A3 6.3 Meter Monopole Configuration Results	83
A4 6.0, 6.5, 7.0 Meter Monopole Results	117

LIST OF FIGURES

FIGURE	PAGE
A-1 Antenna Input Resistance and Reactance versus Frequency in <i>Wet Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	4
A-2 Antenna Input Resistance and Reactance versus Frequency in <i>Moist Clay</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	5
A-3 Antenna Input Resistance and Reactance versus Frequency in <i>Medium Dry Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	6
A-4 Antenna Input Resistance and Reactance versus Frequency in <i>Sandy Soil</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	7
A-5 Antenna Input Resistance and Reactance versus Frequency in <i>Very Dry Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	8
A-6 Antenna Input Resistance and Reactance versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	9
A-7 Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	11
A-8 Antenna Input Resistance and Reactance versus Frequency in <i>Wet Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	13
A-9 Antenna Input Resistance and Reactance versus Frequency in <i>Moist Clay</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	14
A-10 Antenna Input Resistance and Reactance versus Frequency in <i>Medium Dry Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	15
A-11 Antenna Input Resistance and Reactance versus Frequency in <i>Sandy Soil</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	16

FIGURE	PAGE
A-12 Antenna Input Resistance and Reactance versus Frequency in <i>Very Dry Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	17
A-13 Antenna Input Resistance and Reactance versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	18
A-14 Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	20
A-15 Antenna Input Resistance and Reactance versus Frequency and Five Ground Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of Either 16 or 32 Radials	22
A-16 Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding 5.4 Meter High Monopole with 12 Meter Radius Ground Screen Having Either 16 or 32 Radials	23
A-17 Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in <i>Wet Dry Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen	24
A-18 Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in <i>Moist Clay</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen	25
A-19 Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in <i>Medium Dry Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen	26
A-20 Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in <i>Sandy Soil</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen	27
A-21 Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in <i>Very Dry Ground</i> for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen	28
A-22 Antenna Noise Figure (Ohmic Loss) versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials	29

FIGURE	PAGE
A-23 Antenna Noise Figure (Ohmic Loss) versus Frequency and Five Soil Conditions for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i>	30
A-24 Antenna Noise Figure (Ohmic Loss) versus Frequency and Five Soil Conditions for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 or 32 Radials</i>	31
A-25 Cable Attenuation Loss versus Frequency for Four Cable Lengths	42
A-26 System Internal Noise Figure Cumulative Contributions for Case of <i>Wet Ground</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i>	43
A-27 System Internal Noise Figure Cumulative Contributions for Case of <i>Moist Clay</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i>	44
A-28 System Internal Noise Figure Cumulative Contributions for Case of <i>Medium Dry Ground</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i>	45
A-29 System Internal Noise Figure Cumulative Contributions for Case of <i>Sandy Soil</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i>	46
A-30 System Internal Noise Figure Cumulative Contributions for Case of <i>Very Dry Ground</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i>	47
A-31 System Internal Noise Figure versus Frequency, Soil Condition, and Maximum and Minimum Cable Lengths for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i>	48
A-32 System Internal Noise Figure Cumulative Contributions for Case of <i>Wet Ground</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>32 Radials</i>	49
A-33 System Internal Noise Figure Cumulative Contributions for Case of <i>Moist Clay</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>32 Radials</i>	50

FIGURE	PAGE
A-34 System Internal Noise Figure Cumulative Contributions for Case of <i>Medium Dry Ground</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	51
A-35 System Internal Noise Figure Cumulative Contributions for Case of <i>Sandy Soil</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	52
A-36 System Internal Noise Figure Cumulative Contributions for Case of <i>Very Dry Ground</i> and Maximum Length Cable, for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	53
A-37 System Internal Noise Figure versus Frequency, Soil Condition, and Maximum and Minimum Cable Lengths for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	54
A-38 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>5 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	55
A-39 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>10 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	56
A-40 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>15 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	57
A-41 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>20 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	58
A-42 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>25 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	59
A-43 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>30 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	60
A-44 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> for a <i>Wet Ground Condition</i>	61

FIGURE	PAGE
A-45 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> for a <i>Moist Clay Condition</i>	62
A-46 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> for a <i>Medium Dry Ground Condition</i>	63
A-47 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> for a <i>Sandy Soil Condition</i>	64
A-48 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> for a <i>Very Dry Ground Condition</i>	65
A-49 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>5 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	69
A-50 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>10 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	70
A-51 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>15 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	71
A-52 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>20 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	72
A-53 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>25 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	73
A-54 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>30 MHz</i> , for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	74
A-55 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i> for a <i>Wet Ground Condition</i>	75

FIGURE	PAGE
A-56 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i> for a <i>Moist Clay Condition</i>	76
A-57 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i> for a <i>Medium Dry Ground Condition</i>	77
A-58 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i> for a <i>Sandy Soil Condition</i>	78
A-59 Antenna Directivity versus Elevation Angle and Frequency for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i> for a <i>Very Dry Ground Condition</i>	79
A-60 Antenna Input Impedance (Resistance and Reactance) versus Frequency in <i>Wet Ground</i> for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	84
A-61 Antenna Input Impedance (Resistance and Reactance) versus Frequency in <i>Moist Clay</i> for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	85
A-62 Antenna Input Impedance (Resistance and Reactance) versus Frequency in <i>Medium Dry Ground</i> for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	86
A-63 Antenna Input Impedance (Resistance and Reactance) versus Frequency in <i>Sand</i> for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	87
A-64 Antenna Input Impedance (Resistance and Reactance) versus Frequency in <i>Very Dry Ground</i> for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	88
A-65 Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	89
A-66 Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	90

FIGURE	PAGE
A-67 Antenna Noise Figure Ohmic Loss versus Frequency and Five Soil Conditions for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	92
A-68 System Internal Noise Figure Cumulative Contributions for Case of <i>Wet Ground</i> and Maximum Length Cable for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	94
A-69 System Internal Noise Figure Cumulative Contributions for Case of <i>Moist Clay</i> and Maximum Length Cable for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	95
A-70 System Internal Noise Figure Cumulative Contributions for Case of <i>Medium Dry Ground</i> and Maximum Length Cable for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	96
A-71 System Internal Noise Figure Cumulative Contributions for Case of <i>Sandy Soil</i> and Maximum Length Cable for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	97
A-72 System Internal Noise Figure Cumulative Contributions for Case of <i>Very Dry Ground</i> and Maximum Length Cable for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	98
A-73 System Internal Noise Figure versus Frequency, Soil Condition, and Maximum and Minimum Cable Lengths for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radial Wires</i>	99
A-74 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>5 MHz</i> , for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of 16 Radials	100
A-75 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>10 MHz</i> , for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of 16 Radials	101
A-76 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>15 MHz</i> , for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of 16 Radial	102
A-77 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of <i>20 MHz</i> , for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of 16 Radials	103

FIGURE	PAGE
A-78 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 25 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	104
A-79 Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 30 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	105
A-80 Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a <i>Wet Ground</i> Condition	106
A-81 Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a <i>Moist Clay</i> Condition	107
A-82 Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a <i>Medium Dry Ground</i> Condition	108
A-83 Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a <i>Sandy Soil</i> Condition	109
A-84 Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a <i>Very Dry Ground</i> Condition	110
A-85 Antenna Directivity versus Elevation Angle and Five Soil Conditions for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 5 MHz	120
A-86 Antenna Directivity versus Elevation Angle and Five Soil Conditions for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 17.5 MHz	121
A-87 Antenna Directivity versus Elevation Angle and Five Soil Conditions for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 30 MHz	122
A-88 Antenna Directivity versus Elevation Angle and Frequency, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a <i>Wet Ground</i> Condition	123

FIGURE	PAGE
A-89 Antenna Directivity versus Elevation Angle and Frequency, for <i>6.5 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> , for a <i>Moist Clay</i> Condition	124
A-90 Antenna Directivity versus Elevation Angle and Frequency, for <i>6.5 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> , for a <i>Medium Dry Ground</i> Condition	125
A-91 Antenna Directivity versus Elevation Angle and Frequency, for <i>6.5 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> , for a <i>Sandy Soil</i> Condition	126
A-92 Antenna Directivity versus Elevation Angle and Frequency, for <i>6.5 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i> , for a <i>Very Dry Ground</i> Condition	127
A-93 Antenna Directivity versus Elevation Angle and Five Soil Conditions for <i>6.0 Meter</i> High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of <i>30 MHz</i>	128
A-94 Antenna Directivity versus Elevation Angle and Five Soil Conditions for <i>7.0 Meter</i> High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of <i>30 MHz</i>	129

LIST OF TABLES

TABLE	PAGE
A-1 Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried 0.178m Deep	10
A-2 Antenna Input Resistance (ohms), Reactance (ohms), Magnitude Squared of Reflection Coefficient and Mismatch Loss (dB) versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole and 12 Meter Radius Ground Screen of <i>16 Radials</i> and a 75 ohm Feed Cable	12
A-3 Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>32 Radials</i> , 2 mm in Diameter and Buried 0.178 Deep	19
A-4 Antenna Input Resistance (ohms), Reactance (ohms), Magnitude Squared of Reflection Coefficient and Mismatch Loss (dB) versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole and 12 Meter Radius Ground Screen of <i>32 Radials</i> and a 75 ohm Feed Cable	21
A-5 Antenna Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried 0.178m Deep	32
A-6 Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>32 Radials</i> , 2 mm in Diameter and Buried 0.178m Deep	33
A-7 Antenna Input Resistance and Reactance versus Frequency for Four Soil Conditions for 5.4 Meter High Monopole with <i>24 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried 0.178m Deep	34
A-8 Antenna Efficiency and Noise Figure versus Frequency for Four Soil Conditions for 5.4 Meter High Monopole with <i>24 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried 0.178m Deep	35
A-9 Antenna Input Resistance and Reactance versus Frequency for Four Soil Conditions for 5.4 Meter High Monopole with <i>24 Meter</i> Radius Ground Screen of <i>32 Radials</i> , 2 mm in Diameter and Buried 0.178m Deep	36
A-10 Antenna Efficiency and Noise Figure versus Frequency for Four Soil Conditions for 5.4 Meter High Monopole with <i>24 Meter</i> Radius Ground Screen of <i>32 Radials</i> , 2 mm in Diameter and Buried 0.178m Deep	37

TABLE	PAGE
A-11 Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried <i>0.305 Deep</i>	38
A-12 Antenna Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried <i>0.305 Deep</i>	39
A-13 Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>Feed Point Raised 0.2m</i> and with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2mm in Diameter and Buried <i>0.178 Deep</i>	40
A-14 Antenna Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with <i>Feed Point Raised 0.2m</i> and with <i>12 Meter</i> Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried <i>0.178 Deep</i>	41
A-15 Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	66
A-16 Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for <i>5.4 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>32 Radials</i>	80
A-17 Antenna Input Resistance (ohms), Reactance (ohms), Magnitude Squared of Reflection Coefficient ($ \Gamma ^2$), and Mismatch Loss (dB) versus Frequency for Five Soil Conditions for <i>6.3 Meter</i> High Monopole and 12 Meter Radius Ground Screen of <i>16 Radials</i> and a 75 ohm Feed Cable	91
A-18 6.3 Meter High Monopole Antenna: Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 12 Meter Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried <i>0.178 Deep</i>	93
A-19 Antenna Directivity in dBi versus Polar Angle Theta (θ) for Eleven Frequencies and Five Soil Conditions, for <i>6.3 Meter</i> High Monopole with 12 Meter Radius Ground Screen of <i>16 Radials</i>	111
A-20 Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions, for <i>6.0, 6.5, and 7.0 Meter High</i> Monopoles with 12 Meter Radius Ground Screen of <i>16 Radials</i> , 2 mm in Diameter and Buried <i>0.178 Deep</i>	118

TABLE	PAGE
A-21 Antenna Efficiency and Noise versus Frequency for Five Soil Conditions, for 6.0, 6.5, and 7.0 Meter High Monopoles with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178 Deep	119
A-22 Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	130
A-23 Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	133
A-24 Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 7.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials	136

SECTION A1

OVERVIEW

Volume 2—Appendices presents a more comprehensive reference set of theoretical performance results, in tabular and graphical form, for the symmetrical "fat" monopole antenna configuration. The results were obtained from computations using the Numerical Electromagnetics Code—Ground Screen option (NEC-GS). The objective was to provide a more complete reference for investigators interested in a more extensive set of results than was supplied in Volume 1. The results are suitably identified, but presented without elaboration, to serve as an archival reference.

The measures of performance include antenna input impedance, magnitude of the reflection coefficient, cable mismatch loss, antenna efficiency, ohmic loss (noise figure), and directivity. These were examined as a function of monopole antenna dimensions (height and feed height), number, length, and depth of ground screen radial wires, electrical properties (conductivity and relative dielectric constant) of the surrounding earth, and operating frequency across the HF band. The remainder of Volume 2 is organized as follows:

SECTION A2 — 5.4 METER MONOPOLE CONFIGURATION RESULTS

- Antenna input impedance
- Antenna reflection coefficient and cable mismatch loss
- Antenna efficiency and noise figure (ohmic loss)
- Cable attenuation loss
- System internal noise figure
- Directivity

SECTION A3 — 6.3 METER MONOPOLE CONFIGURATION RESULTS

- Antenna input impedance
- Antenna reflection coefficient and cable mismatch loss
- Antenna efficiency and noise figure (ohmic loss)
- Cable attenuation loss
- System internal noise figure
- Directivity

SECTION A4 — 6.0, 6.5, 7.0 METER MONOPOLE RESULTS

- Antenna input impedance
- Antenna efficiency and noise figure (ohmic loss)
- Directivity

SECTION A2

5.4 METER MONOPOLE CONFIGURATION RESULTS




Figure A-1. Antenna Input Resistance and Reactance versus Frequency in Wet Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-2. Antenna Input Resistance and Reactance versus Frequency in Moist Clay for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-3. Antenna Input Resistance and Reactance versus Frequency in Medium Dry Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-4. Antenna Input Resistance and Reactance versus Frequency in Sandy Soil for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-5. Antenna Input Resistance and Reactance versus Frequency in Very Dry Ground for 5.4 Meter
 High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-6. Antenna Input Resistance and Reactance versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

112768-1

Table A-1. Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep
(Supports Vol. 1, Tables 5, 6, 7, 8, 9, 10, & 12)

Frequency (MHz)	Soil Characteristics				
	Very Good (Wet Ground)	Good (Moist Clay)	Average (Medium Dry Ground)	Fair (Sand)	Poor (Very Dry Ground)
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$
5.0	5.26 - j203.9	5.01 - j203.7	5.73 - j201.7	4.79 - j201.7	3.35 - j202.6
7.5	12.2 - j104.6	11.7 - j104.1	14.3 - j102.9	12.4 - j99.5	14.9 - j90.5
10.0	24.6 + j46.3	24.3 - j45.2	27.2 - j47.7	30.6 - j42.2	37.9 - j49.0
12.5	46.1 - j1.19	46.6 + j0.25	49.0 - j1.69	51.4 - j3.62	42.3 - j11.4
15.0	83.3 + j34.1	84.4 + j34.9	84.2 + j32.6	82.0 + j33.8	83.2 + j47.9
17.5	146.0 + j46.1	146.8 + j45.8	145.9 + j46.6	148.1 + j50.4	158.3 + j43.3
20.0	213.4 - j2.56	207.7 - j93.0	211.9 - j2.62	212.5 - j1.49	198.0 - j3.67
22.5	209.3 - j95.1	212.3 - j93.0	211.8 - j91.0	213.2 - j83.6	225.3 - j83.9
25.0	143.7 - j138.4	144.5 - j135.9	147.3 - j138.4	155.6 - j136.6	153.3 - j143.0
27.5	87.5 - j130.3	88.7 - j129.4	89.2 - j131.2	93.1 - j133.1	92.8 - j132.7
30.0	55.7 - j104.9	55.8 - j104.3	56.1 - j105.1	57.8 - j105.8	57.5 - j106.8




Figure A-7. Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

Table A-2. Antenna Input Resistance (ohms), Reactance (ohms), Magnitude Squared of Reflection Coefficient and Mismatch Loss (dB) versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole and 12 Meter Radius Ground Screen of 16 Radials and a 75 ohm Feed Cable

(Supports Vol. 1, Tables 5, 6, 7, 8, 9, 10 & 12)

FREQ	R	X	GAMMA SQ	dB
5.0	5.26	-203.90	9.67137E-01	14.83
7.5	12.20	-104.60	8.02642E-01	7.05
10.0	24.60	-46.30	3.88255E-01	2.13
12.5	46.10	-1.19	5.70429E-02	0.26
15.0	83.30	34.10	4.69725E-02	0.21
17.5	146.00	46.10	1.40607E-01	0.66
20.0	213.40	-2.56	2.30354E-01	1.14
22.5	209.30	-95.10	3.01328E-01	1.56
25.0	143.70	-138.40	3.56416E-01	1.91
27.5	87.50	-130.30	3.94943E-01	2.18
30.0	55.70	-104.90	4.05052E-01	2.26

Wet Ground
 $\epsilon_r = 30, \sigma = 15 \text{ mS/m}$

5.0	5.01	-203.70	9.68619E-01	15.03
7.5	11.70	-104.10	8.08758E-01	7.18
10.0	24.30	-45.20	3.87577E-01	2.13
12.5	46.60	0.25	5.45508E-02	0.24
15.0	84.40	34.90	4.90630E-02	0.22
17.5	146.80	45.80	1.41401E-01	0.66
20.0	212.30	-2.99	2.28470E-01	1.13
22.5	207.70	-93.00	2.96475E-01	1.53
25.0	144.50	-135.90	3.49578E-01	1.87
27.5	88.70	-129.40	3.88867E-01	2.14
30.0	55.80	-104.30	4.01868E-01	2.23

Moist Clay
 $\epsilon_r = 10, \sigma = 15 \text{ mS/m}$

5.0	5.73	-201.70	9.63581E-01	14.39
7.5	14.30	-102.90	7.68894E-01	6.36
10.0	27.20	-47.70	3.58497E-01	1.93
12.5	49.00	-1.69	4.41422E-02	0.20
15.0	84.20	32.60	4.34499E-02	0.19
17.5	146.90	46.60	1.42793E-01	0.67
20.0	211.90	-2.62	2.27755E-01	1.12
22.5	211.80	-91.00	2.98174E-01	1.54
25.0	147.30	-138.40	3.55566E-01	1.91
27.5	89.20	-131.20	3.94229E-01	2.18
30.0	56.10	-105.10	4.03894E-01	2.25

Medium Dry Ground
 $\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$

5.0	4.79	-201.70	9.69458E-01	15.15
7.5	12.40	-99.50	7.87901E-01	6.73
10.0	30.60	-42.20	2.90144E-01	1.49
12.5	51.40	-3.62	3.56512E-02	0.16
15.0	82.00	33.80	4.61952E-02	0.21
17.5	148.10	50.40	1.50702E-01	0.71
20.0	212.50	-1.49	2.28754E-01	1.13
22.5	213.20	-83.60	2.89714E-01	1.49
25.0	155.60	-136.60	3.50186E-01	1.87
27.5	93.10	-133.10	3.92472E-01	2.16
30.0	57.80	-105.80	3.98532E-01	2.21

Sandy Soil
 $\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$

5.0	3.35	-202.60	9.78701E-01	16.72
7.5	14.90	-90.50	7.25299E-01	5.61
10.0	37.90	-49.00	2.49377E-01	1.25
12.5	42.30	-11.40	8.63438E-02	0.39
15.0	83.20	47.90	8.64388E-02	0.39
17.5	158.30	43.30	1.56540E-01	0.74
20.0	198.00	-3.67	2.03139E-01	0.99
22.5	225.30	-83.90	3.04768E-01	1.58
25.0	153.30	-143.00	3.66266E-01	1.98
27.5	92.80	-132.70	3.91690E-01	2.16
30.0	57.50	-106.80	4.04402E-01	2.25

Very Dry Ground
 $\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$




Figure A-8. Antenna Input Resistance and Reactance versus Frequency in Wet Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-9. Antenna Input Resistance and Reactance versus Frequency in Moist Clay for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-10. Antenna Input Resistance and Reactance versus Frequency in Medium Dry Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-11. Antenna Input Resistance and Reactance versus Frequency in Sandy Soil for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-12. Antenna Input Resistance and Reactance versus Frequency in Very Dry Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-13. Antenna Input Resistance and Reactance versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials

L2700-1

Table A-3. Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials, 2 mm in Diameter and Buried 0.178 Deep

(Supports Vol. 1, Tables 5, 7, & 8)

Frequency (MHz)	Soil Characteristics				
	Very Good (Wet Ground)	Good (Moist Clay)	Average (Medium Dry Ground)	Fair (Sand)	Poor (Very Dry Ground)
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$
5.0	3.80 - j192.0	3.66 - j191.9	3.08 - j190.6	2.30 - j190.5	2.85 - j189.7
7.5	10.0 - j91.1	9.64 - j99.2	9.74 - j97.3	7.42 - j96.4	7.79 - j92.8
10.0	22.0 - j43.2	21.6 - j42.8	23.7 - j41.9	22.8 - j38.2	27.5 - j37.2
12.5	43.9 - j0.1	44.1 + j0.51	45.3 - j1.66	49.7 - j0.83	52.3 - j6.05
15.0	83.4 + j32.8	83.4 + j32.3	80.7 + j32.1	77.9 + j26.6	69.4 + j29.0
17.5	149.5 + j35.7	147.8 + j35.6	149.1 + j39.4	139.9 + 48.8	146.3 + j57.6
20.0	202.5 - j29.3	201.8 - j28.4	203.2 - j24.5	215.5 - j27.2	220.5 - j45.4
22.5	174.3 - j107.4	172.9 - j106.3	174.3 - j104.2	169.9 - j104.2	168.3 - j96.4
25.0	114.0 - j129.5	114.1 - j127.7	116.8 - j128.7	126.6 - j123.0	126.0 - j125.3
27.5	69.9 - j116.5	70.6 - j116.1	71.0 - j117.4	75.0 - j119.4	72.2 - j121.7
30.0	45.3 - j93.0	45.2 - j93.1	45.2 - j83.9	45.4 - j94.2	45.3 - j93.8




Figure A-14. Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials

Table A-4. Antenna Input Resistance (ohms), Reactance (ohms), Magnitude Squared of Reflection Coefficient and Mismatch Loss (dB) versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole and 12 Meter Radius Ground Screen of 32 Radials and a 75 ohm Feed Cable

(Supports Vol. 1, Tables 5, 7 & 8)

FREQ	R	X	GAMMA SQ	dB
5.0	3.80	-192.00	9.73534E-01	15.77
7.5	10.00	-91.10	8.06753E-01	7.14
10.0	22.00	-43.20	4.14647E-01	2.33
12.5	43.90	-0.10	6.84166E-02	0.31
15.0	83.40	32.80	4.38119E-02	0.19
17.5	149.50	35.70	1.32071E-01	0.62
20.0	202.50	-29.30	2.19801E-01	1.08
22.5	174.30	-107.40	2.90360E-01	1.49
25.0	114.00	-129.50	3.48463E-01	1.86
27.5	69.90	-116.50	3.93374E-01	2.17
30.0	45.30	-93.00	4.12225E-01	2.31
5.0	3.66	-191.90	9.74473E-01	15.93
7.5	9.64	-99.20	8.29928E-01	7.69
10.0	21.60	-42.80	4.19532E-01	2.36
12.5	44.10	0.51	6.73293E-02	0.30
15.0	83.40	32.30	4.26210E-02	0.19
17.5	147.80	35.60	1.29003E-01	0.60
20.0	201.80	-28.40	2.18080E-01	1.07
22.5	172.90	-106.30	2.87051E-01	1.47
25.0	114.10	-127.70	3.42566E-01	1.82
27.5	70.60	-116.10	3.89248E-01	2.14
30.0	45.20	-93.10	4.13384E-01	2.32
5.0	3.08	-190.60	9.78220E-01	16.62
7.5	9.79	-97.30	8.23674E-01	7.54
10.0	23.70	-41.90	3.81594E-01	2.09
12.5	45.30	-1.66	6.11299E-02	0.27
15.0	80.70	32.10	4.20569E-02	0.19
17.5	149.10	39.40	1.36039E-01	0.64
20.0	203.20	-29.50	2.21113E-01	1.09
22.5	174.30	-104.20	2.83778E-01	1.45
25.0	116.80	-128.70	3.43217E-01	1.83
27.5	71.00	-117.40	3.93141E-01	2.17
30.0	45.20	-83.90	3.68928E-01	2.00
5.0	2.30	-190.50	9.83675E-01	17.87
7.5	7.42	-96.40	8.61619E-01	8.59
10.0	22.80	-38.20	3.79540E-01	2.07
12.5	49.70	-0.83	4.12056E-02	0.18
15.0	77.90	26.60	2.97256E-02	0.13
17.5	139.90	48.80	1.35770E-01	0.63
20.0	215.50	-27.20	2.40574E-01	1.20
22.5	169.90	-104.20	2.80427E-01	1.43
25.0	121.60	-123.00	3.21688E-01	1.69
27.5	75.00	-119.40	3.87861E-01	2.13
30.0	45.40	-94.20	4.17197E-01	2.34
5.0	2.85	-189.70	9.79665E-01	16.92
7.5	7.79	-92.80	8.48895E-01	8.21
10.0	27.50	-37.20	3.06145E-01	1.59
12.5	52.30	-6.05	3.39796E-02	0.15
15.0	69.40	29.00	4.02151E-02	0.18
17.5	146.30	57.60	1.60666E-01	0.76
20.0	220.50	-45.40	2.59913E-01	1.31
22.5	168.30	-96.40	2.62789E-01	1.32
25.0	126.00	-125.30	3.26216E-01	1.71
27.5	72.20	-121.70	4.06229E-01	2.26
30.0	45.30	-93.80	4.16000E-01	2.34

Wet Ground
 $\epsilon_r = 30, \sigma = 15 \text{ mS/m}$

Moist Clay
 $\epsilon_r = 10, \sigma = 15 \text{ mS/m}$

Medium Dry Ground
 $\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$

Sandy Soil
 $\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$

Very Dry Ground
 $\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$




Figure A-15. Antenna Input Resistance and Reactance versus Frequency and Five Ground Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of Either 16 or 32 Radials




Figure A-16. Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding
5.4 Meter High Monopole with 12 Meter Radius Ground Screen Having Either 16 or 32 Radials




Figure A-17. Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in Wet Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen




Figure A-18. Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in Moist Clay for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen




Figure A-19. Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in Medium Dry Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen




Figure A-20. Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in Sandy Soil for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen




Figure A-21. Antenna Noise Figure (Ohmic Loss) versus Frequency and Number of Radials (16 or 32) in Very Dry Ground for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen




Figure A-22. Antenna Noise Figure (Ohmic Loss) versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-23. Antenna Noise Figure (Ohmic Loss) versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-24. Antenna Noise (Ohmic Loss) versus Frequency and Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 or 32 Radials

L2700-6

Table A-5. Antenna Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol. 1, Tables 5, 6, 7, 8, 9, 10 & 12)

Frequency (MHz)	Soil Characteristics									
	Very Good (Wet Ground)		Good (Moist Clay)		Average (Medium Dry Ground)		Fair (Sand)		Poor (Very Dry Ground)	
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$	
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)
5.0	28.9	5.4	29.7	5.3	18.2	7.4	15.3	8.2	20.2	6.9
7.5	29.3	5.3	28.5	5.4	20.5	6.9	19.1	7.2	26.6	5.8
10.0	31.0	5.1	28.7	5.4	22.9	6.4	21.9	6.6	24.7	6.1
12.5	32.1	4.9	28.6	5.4	24.4	6.1	23.8	6.2	28.1	5.5
15.0	32.6	4.9	27.8	5.6	25.0	6.0	22.4	6.5	20.2	6.9
17.5	33.2	4.8	27.0	5.7	25.3	6.0	21.6	6.7	21.3	6.7
20.0	33.7	4.7	26.3	5.8	26.4	5.8	22.5	6.5	23.4	6.3
22.5	34.5	4.6	26.3	5.8	27.8	5.6	24.2	6.2	24.4	6.1
25.0	35.8	4.5	27.1	5.7	30.2	5.2	26.8	5.7	27.7	5.6
27.5	38.1	4.2	29.9	5.2	34.8	4.6	32.4	4.9	33.6	4.7
30.0	42.1	3.8	36.6	4.4	42.4	3.7	42.9	3.7	45.0	3.5

IL2707-1

Table A-6. Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol. 1, Tables 5, 7, & 8)

Frequency (MHz)	Soil Characteristics									
	Very Good (Wet Ground)		Good (Moist Clay)		Average (Medium Dry Ground)		Fair (Sand)		Poor (Very Dry Ground)	
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$	
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)
5.0	39.0	4.1	39.5	4.0	30.1	5.2	29.4	5.3	22.4	6.5
7.5	36.8	4.3	35.1	4.5	30.1	5.2	28.7	5.4	35.7	4.5
10.0	37.3	4.3	34.3	4.6	33.3	4.8	31.1	5.1	36.6	4.4
12.5	37.4	4.3	33.7	4.7	33.9	4.7	34.6	4.6	40.8	3.9
15.0	36.7	4.4	32.4	4.9	32.2	4.9	33.7	4.7	36.5	4.4
17.5	35.9	4.5	30.8	5.1	30.4	5.2	30.0	5.2	30.6	5.1
20.0	35.3	4.5	29.2	5.3	29.9	5.2	28.5	5.4	31.0	5.1
22.5	35.2	4.5	28.4	5.5	29.9	5.2	29.4	5.3	30.4	5.2
25.0	35.8	4.5	28.6	5.4	30.7	5.1	29.8	5.3	30.3	5.2
27.5	38.2	4.2	30.7	5.1	34.1	4.7	32.2	4.9	32.8	4.8
30.0	44.1	3.6	38.0	4.2	43.0	3.7	42.7	3.7	43.9	3.6

Table A-7. Antenna Input Resistance and Reactance versus Frequency for Four Soil Conditions for 5.4 Meter High Monopole with 24 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol. 1, Tables 6 and 8)

Frequency (MHz)	Soil Characteristics			
	Good (Moist Clay)	Average (Medium Dry Ground)	Fair (Sand)	Poor (Very Dry Ground)
	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$
5.0	5.02 - j203.5	6.50 - j202.1	6.21 - j200.5	10.8 - j202.7
10.0	24.2 - j45.2	26.9 - j45.5	27.8 - j43.2	28.5 - j45.1
15.0	84.5 + j35.7	85.3 + j33.6	86.6 + j34.4	86.5 + j32.5
20.0	212.3 - j1.87	211.4 - j1.25	210.4 + j5.58	216.3 + j11.2
25.0	145.8 - j136.5	148.7 - j137.4	154.6 - j136.6	153.1 - j140.1
30.0	56.7 - j104.5	58.4 - j103.8	58.4 - j105.1	58.3 - j106.5

Table A-8. Antenna Efficiency and Noise Figure versus Frequency for Four Soil Conditions for 5.4 Meter High Monopole with 24 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol. 1, Tables 6 and 8)

Frequency (MHz)	Soil Characteristics							
	Good (Moist Clay)		Average (Medium Dry Ground)		Fair (Sand)		Poor (Very Dry Ground)	
	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$	
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)
5.0	30.7	5.1	18.4	7.3	18.3	7.4	19.3	7.2
10.0	29.0	5.4	21.7	6.6	19.2	7.2	18.4	7.3
15.0	27.6	5.6	24.0	6.2	20.3	6.9	20.4	6.9
20.0	26.2	5.8	25.9	5.9	21.6	6.7	22.0	6.6
25.0	26.8	5.7	29.8	5.3	26.1	5.8	27.3	5.6
30.0	36.1	4.4	41.4	3.8	42.5	3.7	44.1	3.6

Table A-9. Antenna Input Resistance and Reactance versus Frequency for Four Soil Conditions for 5.4 Meter High Monopole with 24 Meter Radius Ground Screen of 32 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol. 1, Tables 7 and 8)

Frequency (MHz)	Soil Characteristics			
	Good (Moist Clay)	Average (Medium Dry Ground)	Fair (Sand)	Poor (Very Dry Ground)
	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$
5.0	3.68 - j191.7	3.95 - j190.1	2.84 - j188.9	5.85 - j187.1
10.0	21.4 - j43.1	22.4 - j42.5	21.7 - j40.7	23.9 - j39.9
15.0	83.5 + j33.5	83.5 + j33.4	82.4 + j35.1	83.7 + j35.5
20.0	200.3 - j26.7	201.0 - j24.3	201.0 - j18.1	204.6 - j17.1
25.0	115.2 - j128.1	116.5 - j128.5	120.5 - j128.1	120.7 - j130.4
30.0	46.0 - j92.9	46.3 - j92.2	46.7 - j93.1	46.4 - j93.5

Table A-10. Antenna Efficiency and Noise Figure versus Frequency for Four Soil Conditions, for 5.4 Meter High Monopole with 24 Meter Radius Ground Screen of 32 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol. 1, Tables 7 and 8)

Frequency (MHz)	Soil Characteristics							
	Good (Moist Clay)		Average (Medium Dry Ground)		Fair (Sand)		Poor (Very Dry Ground)	
	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$	
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)
5.0	41.8	3.8	33.9	4.7	39.5	4.0	32.3	4.9
10.0	35.3	4.5	30.3	5.2	29.6	5.3	29.3	5.3
15.0	32.0	5.0	29.5	5.3	27.7	5.6	27.6	5.6
20.0	28.9	5.4	28.4	5.5	25.8	5.9	26.0	5.9
25.0	27.7	5.6	29.4	5.3	26.6	5.8	27.1	5.7
30.0	37.4	4.3	41.8	3.8	41.5	3.8	42.8	3.7

Table A-11. Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.305m Deep

(Supports Vol. 1, Table 9)

Frequency (MHz)	Soil Characteristics				
	Very Good (Wet Ground)	Good (Moist Clay)	Average (Medium Dry Ground)	Fair (Sand)	Poor (Very Dry Ground)
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$
5.0	5.63 - j202.8	5.31 - j202.8	5.97 - j200.3	4.76 - j200.5	3.45 - j200.8
10.0	26.4 - j44.4	25.8 - j43.3	28.8 - j43.2	32.1 - j40.0	39.4 - j47.4
15.0	88.0 + j35.1	88.5 + j36.4	88.9 + j34.8	86.4 + j37.4	91.4 + j53.1
20.0	214.4 - j5.81	214.4 - j5.78	214.2 - j5.28	213.9 - j2.69	197.3 + j1.88
25.0	144.8 - j138.9	146.2 - j136.1	149.2 - j139.0	157.8 - j137.7	154.1 - j143.3
30.0	57.2 - j105.2	57.4 - j103.5	58.0 - j104.1	59.3 - j104.6	58.8 - j105.8

Table A-12. Antenna Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.305m Deep

(Supports Vol. 1, Table 9)

Frequency (MHz)	Soil Characteristics									
	Very Good (Wet Ground)		Good (Moist Clay)		Average (Medium Dry Ground)		Fair (Sand)		Poor (Very Dry Ground)	
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$	
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)
5.0	27.2	5.7	28.3	5.5	17.9	7.5	15.8	8.0	20.4	6.9
10.0	28.8	5.4	27.2	5.7	21.5	6.7	21.3	6.7	24.1	6.2
15.0	29.9	5.2	25.9	5.9	22.8	6.4	20.6	6.9	18.1	7.4
20.0	31.4	5.0	24.5	6.1	24.1	6.2	20.8	6.8	21.5	6.7
25.0	34.6	4.6	25.9	5.9	28.7	5.4	25.5	5.9	26.3	5.8
30.0	40.6	3.9	36.1	4.4	42.4	3.7	43.9	3.6	46.6	3.3

L2708-6

Table A-13. Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with Feed Point Raised 0.2m and with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol.1, Table 10)

Frequency (MHz)	Soil Characteristics				
	Very Good (Wet Ground)	Good (Moist Clay)	Average (Medium Dry Ground)	Fair (Sand)	Poor (Very Dry Ground)
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$	$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$	$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$
5.0	6.26 - j218.2	6.05 - j218.0	7.12 - j217.2	7.21 - j217.9	4.06 - j220.0
10.0	26.5 - j48.2	26.3 - j47.0	29.5 - j47.9	33.5 - j44.3	41.3 - j51.7
15.0	79.6 + j39.2	80.6 + j40.5	81.7 + j38.0	80.8 + j39.6	81.1 + j52.4
20.0	206.7 + j47.9	207.5 + j48.3	208.0 + j45.3	213.7 + j44.5	200.3 + j35.9
25.0	217.8 - j121.5	218.4 - j119.1	220.9 - j121.6	228.1 - j119.9	227.2 - j127.3
30.0	86.7 - j125.3	87.0 - j125.1	87.0 - j126.1	88.0 - j127.6	87.7 - j128.2

L2700-5

Table A-14. Antenna Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 5.4 Meter High Monopole with Feed Point Raised 0.2m and with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep

(Supports Vol. 1, Table 10)

Frequency (MHz)	Soil Characteristics									
	Very Good (Wet Ground)		Good (Moist Clay)		Average (Medium Dry Ground)		Fair (Sand)		Poor (Very Dry Ground)	
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$	
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)
5.0	27.6	5.6	28.0	5.5	16.5	7.8	11.5	9.4	18.6	7.3
10.0	31.1	5.1	28.8	5.4	22.8	6.4	21.5	6.7	24.3	6.2
15.0	32.5	4.9	27.8	5.6	24.7	6.1	22.0	6.6	19.6	7.1
20.0	33.5	4.7	26.3	5.8	25.9	5.9	22.1	6.6	22.7	6.4
25.0	35.5	4.5	27.1	5.7	29.7	5.3	26.1	5.8	26.6	5.8
30.0	42.2	3.7	36.3	4.4	41.8	3.8	41.7	3.8	43.4	3.6




Figure A-25. Cable Attenuation Loss versus Frequency for Four Cable Lengths




Figure A-26. System Internal Noise Figure Cumulative Contributions for Case of Wet Ground and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-27. System Internal Noise Figure Cumulative Contributions for Case of Moist Clay and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-28. System Internal Noise Figure Cumulative Contributions for Case of *Medium Dry Ground* and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-29. System Internal Noise Figure Cumulative Contributions for Case of Sandy Soil and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-30. System Internal Noise Figure Cumulative Contributions for Case of Very Dry Ground and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-31. System Internal Noise Figure versus Frequency, Soil Condition, and Maximum and Minimum Cable Lengths for 5.4 Meter High Monopole with 12 Meter Ground Screen of 16 Radials




Figure A-32. System Internal Noise Figure Cumulative Contributions for Case of Wet Ground and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-33. System Internal Noise Figure Cumulative Contributions for Case of Moist Clay and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-34. System Internal Noise Figure Cumulative Contributions for Case of *Medium Dry Ground* and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-35. System Internal Noise Figure Cumulative Contributions for Case of Sandy Soil and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-36. System Internal Noise Figure Cumulative Contributions for Case of Very Dry Ground and Maximum Length Cable, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-37. System Internal Noise Figure versus Frequency, Soil Condition, and Maximum and Minimum Cable Lengths for 5.4 Meter High Monopole with 12 Meter High Radius Ground Screen of 32 Radials




Figure A-38. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 5 MHz, for 5.4 MeV High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-39. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 10 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-40. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 15 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-41. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 20 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-42. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 25 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-43. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 30 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

Wet Ground $\epsilon=30$ $\sigma=15$

- 16 radials
 ○ = 5 MHz
 △ = 10 MHz
 + = 15 MHz
 × = 20 MHz
 ◊ = 25 MHz
 ▽ = 30 MHz

Conductivity σ , in mS/m




Figure A-44. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials for a Wet Ground Condition




Figure A-45. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials for a Moist Clay Condition




Figure A-46. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials for a Medium Dry Ground Condition




Figure A-47. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials for a Sandy Soil Condition

Very Dry Ground $\epsilon=4$ $\sigma=0.15$

16 radials

\circ = 5 MHz
 Δ = 10 MHz
 $+$ = 15 MHz
 \times = 20 MHz
 \diamond = 25 MHz
 ∇ = 30 MHz

Conductivity σ , in mS/m




Figure A-48. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials for a Very Dry Ground Condition

Table A-15. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

		[Elevation Angle $\psi = 90^\circ - \theta$]									
		Wet Ground $\epsilon_r = 30, \sigma = 15 \text{ mS/m}$									
THETA		5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz				
0.0	0.0	-86.64	-86.95	-87.18	-87.32	-87.58	-88.29	THETA	5 MHz	10 MHz	15 MHz
2.5	2.5	-20.54	-20.76	-22.13	-25.41	-25.92	-20.17	0.0	-86.78	-86.62	-86.48
5.0	5.0	-14.53	-14.75	-16.11	-19.35	-19.92	-14.18	2.5	-20.55	-20.57	-21.48
7.5	7.5	-11.03	-11.24	-12.57	-15.76	-16.43	-10.72	5.0	-14.53	-14.55	-15.46
10.0	10.0	-8.55	-8.75	-10.06	-13.17	-13.97	-8.31	7.5	-11.03	-11.04	-11.94
12.5	12.5	-6.64	-6.83	-8.10	-11.11	-12.08	-6.49	10.0	-8.55	-8.56	-9.43
15.0	15.0	-5.09	-5.27	-6.50	-9.39	-10.54	-5.05	12.5	-6.64	-6.64	-7.49
17.5	17.5	-3.80	-3.96	-5.14	-7.90	-9.23	-3.89	15.0	-5.09	-5.08	-5.90
20.0	20.0	-2.68	-2.84	-3.96	-6.57	-8.08	-2.94	17.5	-3.80	-3.78	-4.56
22.5	22.5	-1.72	-1.85	-2.91	-5.37	-7.04	-2.16	20.0	-2.68	-2.65	-3.39
25.0	25.0	-0.87	-0.98	-1.98	-4.27	-6.07	-1.52	22.5	-1.72	-1.67	-2.37
27.5	27.5	-0.11	-0.21	-1.13	-3.24	-5.14	-1.00	25.0	-0.87	-0.81	-1.46
30.0	30.0	0.57	0.49	-0.36	-2.29	-4.25	-0.58	27.5	-0.11	-0.03	-0.63
32.5	32.5	1.17	1.12	0.35	-1.41	-3.37	-0.24	30.0	0.57	0.66	0.11
35.0	35.0	1.72	1.68	1.00	-0.57	-2.50	0.03	32.5	1.18	1.28	0.79
37.5	37.5	2.21	2.20	1.59	0.20	-1.64	0.27	35.0	1.72	1.84	1.41
40.0	40.0	2.66	2.66	2.14	0.93	-0.79	0.48	37.5	2.22	2.35	1.98
42.5	42.5	3.06	3.08	2.64	1.61	0.04	0.71	40.0	2.66	2.81	2.50
45.0	45.0	3.41	3.46	3.09	2.24	0.84	0.98	42.5	3.06	3.22	2.97
47.5	47.5	3.73	3.79	3.51	2.82	1.61	1.31	45.0	3.42	3.59	3.40
50.0	50.0	4.01	4.09	3.88	3.35	2.34	1.72	47.5	3.74	3.92	3.78
52.5	52.5	4.25	4.34	4.21	3.84	3.03	2.20	50.0	4.02	4.20	4.12
55.0	55.0	4.45	4.55	4.49	4.27	3.66	2.74	52.5	4.26	4.45	4.42
57.5	57.5	4.62	4.73	4.73	4.64	4.23	3.32	55.0	4.46	4.65	4.67
60.0	60.0	4.75	4.85	4.92	4.96	4.74	3.01	57.5	4.63	4.81	4.88
62.5	62.5	4.83	4.93	5.06	5.21	5.17	4.47	60.0	4.75	4.92	5.03
65.0	65.0	4.86	4.96	5.13	5.40	5.52	4.97	62.5	4.84	4.98	5.12
67.5	67.5	4.84	4.92	5.14	5.50	5.78	5.40	65.0	4.87	4.98	5.15
70.0	70.0	4.76	4.81	5.06	5.51	5.93	5.71	67.5	4.76	4.78	5.10
72.5	72.5	4.59	4.60	4.89	5.41	5.94	5.89	70.0	4.76	4.76	5.45
75.0	75.0	4.31	4.27	4.58	5.16	5.80	5.89	72.5	4.59	4.54	5.26
77.5	77.5	3.88	3.77	4.08	4.72	5.45	5.66	75.0	4.30	4.16	4.32
80.0	80.0	3.22	3.01	3.32	3.99	4.79	5.10	77.5	3.86	3.60	3.72
82.5	82.5	2.15	1.82	2.11	2.80	3.65	4.04	80.0	3.18	2.76	2.82
85.0	85.0	0.28	-0.22	0.03	0.73	1.61	2.06	82.5	2.08	1.45	1.43
87.5	87.5	-3.79	-4.52	-4.32	-3.64	-2.74	-2.27	85.0	0.14	-0.77	-0.89
90.0	90.0	-86.64	-86.95	-87.18	-87.32	-87.58	-88.29	87.5	-4.07	-5.34	-5.60
								90.0	-86.78	-86.62	-86.48

[Elevation Angle $\psi = 90^\circ - \theta$]

Moist Clay $\epsilon_r = 10, \sigma = 15 \text{ mS/m}$

THETA		5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz
0.0	0.0	-86.78	-86.62	-86.48	-86.25	-86.38	-87.67
2.5	2.5	-20.55	-20.57	-21.48	-25.15	-24.49	-18.70
5.0	5.0	-14.53	-14.55	-15.46	-19.08	-18.51	-12.72
7.5	7.5	-11.03	-11.04	-11.94	-15.47	-15.04	-9.28
10.0	10.0	-8.55	-8.56	-9.43	-12.87	-12.62	-6.88
12.5	12.5	-6.64	-6.64	-7.49	-10.79	-10.76	-5.07
15.0	15.0	-5.09	-5.08	-5.90	-9.05	-9.26	-3.65
17.5	17.5	-3.80	-3.78	-4.56	-7.54	-8.00	-2.51
20.0	20.0	-2.68	-2.65	-3.39	-6.19	-6.90	-1.57
22.5	22.5	-1.72	-1.67	-2.37	-4.97	-5.91	-0.81
25.0	25.0	-0.87	-0.81	-1.46	-3.85	-5.00	-0.18
27.5	27.5	-0.11	-0.03	-0.63	-2.82	-4.12	0.34
30.0	30.0	0.57	0.66	0.11	-1.86	-3.28	0.76
32.5	32.5	1.18	1.28	0.79	-0.97	-2.45	1.10
35.0	35.0	1.72	1.84	1.41	-0.14	-1.63	1.38
37.5	37.5	2.22	2.35	1.98	0.63	-0.82	1.62
40.0	40.0	2.66	2.81	2.50	1.35	-0.02	1.82
42.5	42.5	3.06	3.22	2.97	2.02	0.75	2.03
45.0	45.0	3.42	3.59	3.40	2.63	1.50	2.25
47.5	47.5	3.74	3.92	3.78	3.19	2.22	2.49
50.0	50.0	4.02	4.20	4.12	3.69	2.89	2.79
52.5	52.5	4.26	4.45	4.42	4.15	3.52	3.12
55.0	55.0	4.46	4.65	4.67	4.54	4.09	3.50
57.5	57.5	4.63	4.81	4.88	4.88	4.59	3.90
60.0	60.0	4.75	4.92	5.03	5.15	5.03	4.31
62.5	62.5	4.84	4.98	5.12	5.36	5.39	4.69
65.0	65.0	4.87	4.98	5.15	5.48	5.66	5.02
67.5	67.5	4.85	4.92	5.10	5.52	5.82	5.27
70.0	70.0	4.76	4.78	5.45	5.87	5.87	5.42
72.5	72.5	4.59	4.54	5.26	5.78	5.78	5.42
75.0	75.0	4.30	4.16	4.32	4.90	5.50	5.24
77.5	77.5	3.86	3.60	3.72	4.33	4.99	4.81
80.0	80.0	3.18	2.76	2.82	3.44	4.14	4.03
82.5	82.5	2.08	1.45	1.43	2.03	2.76	2.69
85.0	85.0	0.14	-0.77	-0.89	0.33	0.40	0.36
87.5	87.5	-4.07	-5.34	-5.60	-5.10	-4.39	-4.43
90.0	90.0	-86.78	-86.62	-86.48	-86.25	-86.38	-87.67

Table A-15. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Continued)

[Elevation Angle $\psi = 90^\circ - \theta$]													
Sand $\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$													
THETA	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz	THETA	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz
0.0	-84.63	-85.63	-86.02	-86.25	-86.85	-88.31	0.0	-83.88	-85.45	-85.55	-85.57	-86.32	-88.36
2.5	-19.38	-19.62	-21.19	-25.98	-23.75	-19.24	2.5	-19.13	-18.54	-19.77	-30.41	-20.75	-18.93
5.0	-13.37	-13.61	-15.17	-19.88	-17.77	-13.27	5.0	-13.12	-12.54	-13.76	-24.16	-14.82	-12.95
7.5	-9.87	-10.11	-11.64	-16.25	-14.31	-9.83	7.5	-9.62	-9.04	-10.26	-20.26	-11.45	-9.48
10.0	-7.40	-7.64	-9.13	-13.60	-11.89	-7.44	10.0	-7.15	-6.59	-7.79	-17.27	-9.15	-7.07
12.5	-5.50	-5.73	-7.19	-11.47	-10.04	-5.64	12.5	-5.25	-4.70	-5.89	-14.75	-7.46	-5.24
15.0	-3.97	-4.19	-5.60	-9.66	-8.55	-4.23	15.0	-3.72	-3.19	-4.35	-12.52	-6.16	-3.79
17.5	-2.68	-2.90	-4.25	-8.07	-7.31	-3.09	17.5	-2.43	-1.93	-3.06	-10.51	-5.13	-2.61
20.0	-1.59	-1.79	-3.08	-6.65	-6.24	-2.16	20.0	-1.34	-0.86	-1.95	-8.67	-4.28	-1.63
22.5	-0.64	-0.84	-2.05	-5.34	-5.28	-1.40	22.5	-0.40	0.06	-0.99	-6.99	-3.56	-0.82
25.0	0.19	0.01	-1.14	-4.14	-4.41	-0.76	25.0	0.43	0.86	-0.15	-5.43	-2.92	-0.14
27.5	0.92	0.75	-0.31	-3.03	-3.58	-0.24	27.5	1.16	1.56	0.61	-4.01	-2.31	0.42
30.0	1.57	1.41	0.44	-2.00	-2.78	0.19	30.0	1.80	2.17	1.28	-2.70	-1.71	0.90
32.5	2.14	2.00	1.12	-1.04	-2.00	0.56	32.5	2.38	2.71	1.89	-1.51	-1.09	1.29
35.0	2.65	2.53	1.73	-0.15	-1.23	0.87	35.0	2.88	3.18	2.44	-0.42	-0.46	1.64
37.5	3.11	3.00	2.30	0.67	-0.46	1.16	37.5	3.33	3.59	2.93	0.57	0.20	1.94
40.0	3.51	3.41	2.81	1.44	0.29	1.43	40.0	3.72	3.95	3.38	1.46	0.88	2.22
42.5	3.86	3.78	3.27	2.14	1.04	1.72	42.5	4.06	4.26	3.77	2.26	1.55	2.50
45.0	4.16	4.10	3.69	2.78	1.75	2.02	45.0	4.35	4.51	4.12	2.98	2.22	2.79
47.5	4.42	4.37	4.06	3.36	2.44	2.37	47.5	4.60	4.72	4.42	3.61	2.87	3.09
50.0	4.63	4.60	4.38	3.87	3.09	2.76	50.0	4.79	4.88	4.67	4.16	3.47	3.42
52.5	4.80	4.79	4.65	4.33	3.69	3.18	52.5	4.94	5.00	4.88	4.63	4.03	3.76
55.0	4.92	4.92	4.87	4.72	4.23	3.63	55.0	5.04	5.06	5.03	5.02	4.53	4.11
57.5	4.99	5.01	5.04	5.05	4.71	4.08	57.5	5.08	5.07	5.13	5.33	4.95	4.46
60.0	5.01	5.04	5.15	5.30	5.12	4.51	60.0	5.07	5.02	5.17	5.56	5.30	4.77
62.5	4.97	5.01	5.19	5.48	5.45	4.90	62.5	4.99	4.91	5.14	5.69	5.56	5.04
65.0	4.86	4.91	5.17	5.57	5.68	5.23	65.0	4.84	4.73	5.03	5.73	5.72	5.24
67.5	4.68	4.74	5.05	5.57	5.81	5.16	67.5	4.61	4.46	4.83	5.65	5.77	5.34
70.0	4.41	4.47	4.84	5.45	5.82	5.18	70.0	4.28	4.09	4.52	5.46	5.68	5.32
72.5	4.02	4.09	4.51	5.20	5.68	5.54	72.5	3.81	3.60	4.08	5.11	5.43	5.14
75.0	3.48	3.54	4.01	4.77	5.35	5.32	75.0	3.19	2.93	3.46	4.57	4.98	4.76
77.5	2.73	2.79	3.29	4.11	4.77	4.83	77.5	2.34	2.04	2.61	3.78	4.27	4.11
80.0	1.67	1.72	2.25	3.13	3.85	3.99	80.0	1.15	0.81	1.41	2.64	3.19	3.09
82.5	0.10	0.15	0.70	1.61	2.39	2.59	82.5	-0.56	-0.95	-0.33	0.94	1.54	1.49
85.0	-2.41	-2.38	-1.81	-0.88	-0.06	0.19	85.0	-3.26	-3.71	-3.07	-1.77	-1.14	-1.16
87.5	-7.33	-7.32	-6.74	-5.79	-4.95	-4.68	87.5	-8.42	-8.92	-8.28	-6.96	-6.31	-6.31
90.0	-84.63	-85.63	-86.02	-86.25	-86.85	-88.31	90.0	-83.88	-85.45	-85.55	-85.57	-86.32	-88.36

[Elevation Angle $\psi = 90^\circ - \theta$]

Sand $\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$

Table A-15. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Concluded)

THETA	[Elevation Angle $\psi = 90^\circ - \theta$]									
	Very Dry Ground $\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$									
	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz	30 MHz	30 MHz	30 MHz	30 MHz
0.0	-85.09	-85.96	-85.09	-85.73	-86.46	-88.58	-88.58	-88.58	-88.58	-88.58
2.5	-18.90	-17.99	-21.80	-25.84	-20.11	-20.31	-20.31	-20.31	-20.31	-20.31
5.0	-12.90	-11.99	-15.80	-19.92	-14.18	-14.28	-14.28	-14.28	-14.28	-14.28
7.5	-9.40	-8.51	-12.29	-16.55	-10.80	-10.75	-10.75	-10.75	-10.75	-10.75
10.0	-6.93	-6.07	-9.82	-14.24	-8.50	-8.24	-8.24	-8.24	-8.24	-8.24
12.5	-5.04	-4.20	-7.90	-12.47	-6.80	-6.30	-6.30	-6.30	-6.30	-6.30
15.0	-3.51	-2.70	-6.34	-11.00	-5.50	-4.73	-4.73	-4.73	-4.73	-4.73
17.5	-2.23	-1.46	-5.01	-9.68	-4.47	-3.42	-3.42	-3.42	-3.42	-3.42
20.0	-1.14	-0.41	-3.86	-8.41	-3.63	-2.31	-2.31	-2.31	-2.31	-2.31
22.5	-0.21	0.48	-2.82	-7.13	-2.94	-1.38	-1.38	-1.38	-1.38	-1.38
25.0	0.61	1.26	-1.88	-5.84	-2.33	-0.58	-0.58	-0.58	-0.58	-0.58
27.5	1.33	1.93	-1.02	-4.55	-1.79	0.10	0.10	0.10	0.10	0.10
30.0	1.97	2.51	-0.21	-3.28	-1.27	0.68	0.68	0.68	0.68	0.68
32.5	2.53	3.02	0.54	-2.07	-0.75	1.18	1.18	1.18	1.18	1.18
35.0	3.03	3.45	1.24	-0.92	-0.22	1.60	1.60	1.60	1.60	1.60
37.5	3.46	3.83	1.89	0.14	0.34	1.97	1.97	1.97	1.97	1.97
40.0	3.84	4.16	2.50	1.11	0.93	2.30	2.30	2.30	2.30	2.30
42.5	4.17	4.43	3.05	1.99	1.53	2.62	2.62	2.62	2.62	2.62
45.0	4.45	4.65	3.56	2.78	2.15	2.92	2.92	2.92	2.92	2.92
47.5	4.68	4.82	4.01	3.47	2.76	3.23	3.23	3.23	3.23	3.23
50.0	4.86	4.95	4.41	4.08	3.35	3.55	3.55	3.55	3.55	3.55
52.5	4.99	5.03	4.75	4.59	3.90	3.87	3.87	3.87	3.87	3.87
55.0	5.07	5.06	5.02	5.02	4.41	4.20	4.20	4.20	4.20	4.20
57.5	5.10	5.03	5.23	5.35	4.85	4.52	4.52	4.52	4.52	4.52
60.0	5.07	4.96	5.37	5.60	5.22	4.81	4.81	4.81	4.81	4.81
62.5	4.97	4.82	5.43	5.75	5.50	5.06	5.06	5.06	5.06	5.06
65.0	4.80	4.60	5.40	5.80	5.68	5.24	5.24	5.24	5.24	5.24
67.5	4.54	4.31	5.28	5.74	5.75	5.33	5.33	5.33	5.33	5.33
70.0	4.18	3.91	5.03	5.55	5.68	5.29	5.29	5.29	5.29	5.29
72.5	3.68	3.39	4.64	5.21	5.45	5.11	5.11	5.11	5.11	5.11
75.0	3.02	2.70	4.06	4.67	5.01	4.72	4.72	4.72	4.72	4.72
77.5	2.13	1.79	3.24	3.88	4.31	4.07	4.07	4.07	4.07	4.07
80.0	0.90	0.54	2.07	2.74	3.24	3.04	3.04	3.04	3.04	3.04
82.5	-0.87	-1.24	0.35	1.04	1.60	1.43	1.43	1.43	1.43	1.43
85.0	-3.63	-4.01	-2.38	-1.67	-1.07	-1.21	-1.21	-1.21	-1.21	-1.21
87.5	-8.85	-9.24	-7.58	-6.87	-6.24	-6.36	-6.36	-6.36	-6.36	-6.36
90.0	-85.09	-85.96	-85.09	-85.73	-86.46	-88.58	-88.58	-88.58	-88.58	-88.58




Figure A-49. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 5 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-50. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 10 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-51. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 15 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-52. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 20 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-53. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 25 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-54. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 30 MHz, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials




Figure A-55. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials for a Wet Ground Condition




Figure A-56. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials for a Moist Clay Condition




Figure A-57. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials for a Medium Dry Ground Condition




Figure A-58. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials for a Sandy Soil Condition

Very Dry Ground $\epsilon=4$ $\sigma=0.15$

32 radials
 0 = 5 MHz
 4 = 10 MHz
 + = 15 MHz
 x = 20 MHz
 o = 25 MHz
 v = 30 MHz

Conductivity σ , in mS/m




Figure A-59. Antenna Directivity versus Elevation Angle and Frequency for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials for a Very Dry Ground Condition

Table A-16. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials

[Elevation Angle $\psi = 90^\circ - \theta$]													
Moist Clay $\epsilon_r = 10, \sigma = 15 \text{ mS/m}$													
	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz		5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz
THETA	0.0	-91.01	-90.41	-90.16	-89.71	-89.61	0.0	-91.01	-90.41	-90.16	-89.71	-89.61	-90.85
	2.5	-20.54	-20.47	-21.11	-26.24	-24.02	2.5	-20.54	-20.47	-21.11	-26.24	-24.02	-17.87
	5.0	-14.53	-14.46	-15.09	-20.15	-18.08	5.0	-14.53	-14.46	-15.09	-20.15	-18.08	-11.90
	7.5	-11.03	-10.95	-11.57	-16.50	-14.68	7.5	-11.03	-10.95	-11.57	-16.50	-14.68	-8.47
	10.0	-8.55	-8.47	-9.08	-13.83	-12.34	10.0	-8.55	-8.47	-9.08	-13.83	-12.34	-6.09
	12.5	-6.64	-6.55	-7.15	-11.69	-10.60	12.5	-6.64	-6.55	-7.15	-11.69	-10.60	-4.31
	15.0	-5.09	-5.00	-5.57	-9.87	-9.22	15.0	-5.09	-5.00	-5.57	-9.87	-9.22	-2.92
	17.5	-3.79	-3.70	-4.25	-8.27	-8.09	17.5	-3.79	-3.70	-4.25	-8.27	-8.09	-1.81
	20.0	-2.68	-2.58	-3.10	-6.84	-7.12	20.0	-2.68	-2.58	-3.10	-6.84	-7.12	-0.91
	22.5	-1.71	-1.60	-2.10	-5.53	-6.25	22.5	-1.71	-1.60	-2.10	-5.53	-6.25	-0.18
	25.0	-0.86	-0.74	-1.20	-4.33	-5.43	25.0	-0.86	-0.74	-1.20	-4.33	-5.43	0.40
	27.5	-0.10	0.03	-0.40	-3.22	-4.62	27.5	-0.10	0.03	-0.40	-3.22	-4.62	0.86
	30.0	0.57	0.71	0.32	-2.19	-3.81	30.0	0.57	0.71	0.32	-2.19	-3.81	1.22
	32.5	1.18	1.33	0.98	-1.24	-2.97	32.5	1.18	1.33	0.98	-1.24	-2.97	1.50
	35.0	1.73	1.89	1.58	-0.35	-2.12	35.0	1.73	1.89	1.58	-0.35	-2.12	1.70
	37.5	2.22	2.39	2.12	0.47	-1.26	37.5	2.22	2.39	2.12	0.47	-1.26	1.86
	40.0	2.67	2.84	2.62	1.23	-0.40	40.0	2.67	2.84	2.62	1.23	-0.40	1.98
	42.5	3.07	3.25	3.07	1.93	0.45	42.5	3.07	3.25	3.07	1.93	0.45	2.10
	45.0	3.43	3.61	3.48	2.57	1.26	45.0	3.43	3.61	3.48	2.57	1.26	2.24
	47.5	3.74	3.93	3.85	3.16	2.04	47.5	3.74	3.93	3.85	3.16	2.04	2.43
	50.0	4.02	4.21	4.17	3.69	2.77	50.0	4.02	4.21	4.17	3.69	2.77	2.67
	52.5	4.27	4.45	4.45	4.15	3.44	52.5	4.27	4.45	4.45	4.15	3.44	2.97
	55.0	4.47	4.64	4.68	4.56	4.05	55.0	4.47	4.64	4.68	4.56	4.05	3.34
	57.5	4.64	4.80	4.87	4.91	4.59	57.5	4.64	4.80	4.87	4.91	4.59	3.74
	60.0	4.76	4.91	5.01	5.19	5.05	60.0	4.76	4.91	5.01	5.19	5.05	4.16
	62.5	4.84	4.96	5.09	5.39	5.42	62.5	4.84	4.96	5.09	5.39	5.42	4.56
	65.0	4.88	4.96	5.11	5.52	5.71	65.0	4.88	4.96	5.11	5.52	5.71	4.92
	67.5	4.86	4.90	5.05	5.56	5.89	67.5	4.86	4.90	5.05	5.56	5.89	5.20
	70.0	4.77	4.75	4.91	5.50	5.94	70.0	4.77	4.75	4.91	5.50	5.94	5.37
	72.5	4.60	4.51	4.65	5.30	5.85	72.5	4.60	4.51	4.65	5.30	5.85	5.39
	75.0	4.31	4.13	4.25	4.94	5.58	75.0	4.31	4.13	4.25	4.94	5.58	5.23
	77.5	3.87	3.56	3.64	4.37	5.08	77.5	3.87	3.56	3.64	4.37	5.08	4.82
	80.0	3.19	2.72	2.74	3.47	4.23	80.0	3.19	2.72	2.74	3.47	4.23	4.04
	82.5	2.09	1.41	1.35	2.07	2.85	82.5	2.09	1.41	1.35	2.07	2.85	2.72
	85.0	0.15	-0.81	-0.98	-0.29	0.49	85.0	0.15	-0.81	-0.98	-0.29	0.49	0.39
	87.5	-4.06	-5.38	-5.69	-5.06	-4.30	87.5	-4.06	-5.38	-5.69	-5.06	-4.30	-4.39
	90.0	-91.01	-90.41	-90.16	-89.71	-89.61	90.0	-91.01	-90.41	-90.16	-89.71	-89.61	-90.85

[Elevation Angle $\psi = 90^\circ - \theta$]													
Wet Ground $\epsilon_r = 30, \sigma = 15 \text{ mS/m}$													
	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz		5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz
THETA	0.0	-90.96	-90.77	-90.69	-90.53	-91.49	0.0	-90.96	-90.77	-90.69	-90.53	-90.59	-91.49
	2.5	-20.55	-20.65	-22.10	-26.41	-25.18	2.5	-20.55	-20.65	-22.10	-26.41	-25.18	-19.57
	5.0	-14.54	-14.63	-16.07	-20.33	-19.20	5.0	-14.54	-14.63	-16.07	-20.33	-19.20	-13.58
	7.5	-11.03	-11.12	-12.54	-16.71	-15.76	7.5	-11.03	-11.12	-12.54	-16.71	-15.76	-10.12
	10.0	-8.55	-8.64	-10.03	-14.08	-13.36	10.0	-8.55	-8.64	-10.03	-14.08	-13.36	-7.70
	12.5	-6.64	-6.73	-8.07	-11.97	-11.54	12.5	-6.64	-6.73	-8.07	-11.97	-11.54	-5.87
	15.0	-5.09	-5.17	-6.47	-10.20	-10.08	15.0	-5.09	-5.17	-6.47	-10.20	-10.08	-4.42
	17.5	-3.80	-3.86	-5.11	-8.64	-8.87	17.5	-3.80	-3.86	-5.11	-8.64	-8.87	-3.25
	20.0	-2.69	-2.74	-3.93	-7.24	-7.83	20.0	-2.69	-2.74	-3.93	-7.24	-7.83	-2.29
	22.5	-1.72	-1.76	-2.88	-5.97	-6.89	22.5	-1.72	-1.76	-2.88	-5.97	-6.89	-1.50
	25.0	-0.87	-0.90	-1.95	-4.80	-6.03	25.0	-0.87	-0.90	-1.95	-4.80	-6.03	-0.86
	27.5	-0.11	-0.13	-1.10	-3.71	-5.20	27.5	-0.11	-0.13	-1.10	-3.71	-5.20	-0.35
	30.0	0.57	0.56	-0.33	-2.70	-4.38	30.0	0.57	0.56	-0.33	-2.70	-4.38	0.06
	32.5	1.17	1.18	0.37	-1.75	-3.56	32.5	1.17	1.18	0.37	-1.75	-3.56	0.37
	35.0	1.72	1.74	1.02	-0.86	-2.72	35.0	1.72	1.74	1.02	-0.86	-2.72	0.61
	37.5	2.21	2.25	1.61	-0.04	-1.88	37.5	2.21	2.25	1.61	-0.04	-1.88	0.79
	40.0	2.66	2.71	2.16	0.74	-1.04	40.0	2.66	2.71	2.16	0.74	-1.04	0.94
	42.5	3.06	3.12	2.66	1.46	-0.20	42.5	3.06	3.12	2.66	1.46	-0.20	1.09
	45.0	3.41	3.49	3.11	2.12	0.63	45.0	3.41	3.49	3.11	2.12	0.63	1.27
	47.5	3.73	3.82	3.52	2.74	1.43	47.5	3.73	3.82	3.52	2.74	1.43	1.50
	50.0	4.01	4.11	3.89	3.30	2.19	50.0	4.01	4.11	3.89	3.30	2.19	1.81
	52.5	4.25	4.35	4.22	3.80	2.91	52.5	4.25	4.35	4.22	3.80	2.91	2.21
	55.0	4.45	4.56	4.50	4.25	3.58	55.0	4.45	4.56	4.50	4.25	3.58	2.69
	57.5	4.62	4.73	4.74	4.65	4.18	57.5	4.62	4.73	4.74	4.65	4.18	3.23
	60.0	4.75	4.85	4.93	4.98	4.71	60.0	4.75	4.85	4.93	4.98	4.71	3.79
	62.5	4.83	4.92	5.06	5.24	5.17	62.5	4.83	4.92	5.06	5.24	5.17	4.34
	65.0	4.86	4.94	5.14	5.44	5.54	65.0	4.86	4.94	5.14	5.44	5.54	4.85
	67.5	4.84	4.90	5.14	5.55	5.81	67.5	4.84	4.90	5.14	5.55	5.81	5.28
	70.0	4.76	4.79	5.06	5.57	5.98	70.0	4.76	4.79	5.06	5.57	5.98	5.60
	72.5	4.59	4.58	4.88	5.47	6.01	72.5	4.59	4.58	4.88	5.47	6.01	5.79
	75.0	4.31	4.25	4.57	5.23	5.88	75.0	4.31	4.25	4.57	5.23	5.88	5.80
	77.5	3.88	3.74	4.08	4.79	5.53	77.5	3.88	3.74	4.08	4.79	5.53	5.58
	80.0	3.22	2.98	3.32	4.06	4.88	80.0	3.22	2.98	3.32	4.06	4.88	5.04
	82.5	2.15	1.79	2.11	2.88	3.75	82.5	2.15	1.79	2.11	2.88	3.75	3.99
	85.0	0.28	-0.25	0.03	0.81	1.71	85.0	0.28	-0.25	0.03	0.81	1.71	2.01
	87.5	-3.79	-4.55	-4.33	-3.56	-2.64	87.5	-3.79	-4.55	-4.33	-3.56	-2.64	-2.32
	90.0	-90.96	-90.77	-90.69	-90.53	-91.49	90.0	-90.96	-90.77	-90.69	-90.53	-90.59	-91.49

[Elevation Angle $\psi = 90^\circ - \theta$]

Moist Clay $\epsilon_r = 10, \sigma = 15 \text{ mS/m}$

Table A-16. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials (Continued)

		[Elevation Angle $\psi = 90^\circ - \theta$]									
		Sand $\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$									
THETA	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz	THETA	5 MHz	10 MHz	15 MHz	20 MHz
0.0	-89.83	-90.28	-90.13	-89.81	-89.93	-91.38	0.0	-89.74	-89.98	-90.33	-89.60
2.5	-19.42	-19.17	-20.62	-31.03	-21.73	-18.68	2.5	-19.16	-18.42	-17.84	-28.17
5.0	-13.41	-13.17	-14.61	-24.76	-15.82	-12.70	5.0	-13.15	-12.42	-11.85	-22.29
7.5	-9.91	-9.67	-11.10	-20.86	-12.47	-9.24	7.5	-9.65	-8.93	-8.38	-18.98
10.0	-7.44	-7.20	-8.61	-17.86	-10.21	-6.83	10.0	-7.18	-6.48	-5.96	-16.72
12.5	-5.54	-5.31	-6.69	-15.34	-8.57	-5.00	12.5	-5.28	-4.60	-4.11	-14.96
15.0	-4.00	-3.78	-5.13	-13.12	-7.32	-3.56	15.0	-3.74	-3.08	-2.64	-13.44
17.5	-2.72	-2.51	-3.81	-11.11	-6.36	-2.40	17.5	-2.46	-1.83	-1.43	-11.96
20.0	-1.62	-1.43	-2.68	-9.28	-5.58	-1.44	20.0	-1.37	-0.77	-0.42	-10.42
22.5	-0.67	-0.49	-1.68	-7.59	-4.93	-0.66	22.5	-0.42	0.15	0.44	-8.82
25.0	0.16	0.33	-0.80	-6.04	-4.35	-0.03	25.0	0.41	0.94	1.18	-7.19
27.5	0.89	1.05	-0.01	-4.61	-3.79	0.48	27.5	1.14	1.63	1.82	-5.59
30.0	1.54	1.68	0.70	-3.30	-3.21	0.88	30.0	1.78	2.24	2.38	-4.06
32.5	2.12	2.25	1.35	-2.09	-1.90	1.19	32.5	2.36	2.77	2.64	-2.65
35.0	2.63	2.74	1.93	-0.99	-1.90	1.43	35.0	2.86	3.23	3.29	-1.33
37.5	3.09	3.19	2.47	0.02	-1.15	1.61	37.5	3.31	3.64	3.66	-0.14
40.0	3.49	3.57	2.95	0.94	-0.37	1.76	40.0	3.71	3.99	3.98	0.92
42.5	3.85	3.91	3.38	1.77	0.44	1.90	42.5	4.05	4.29	4.25	1.87
45.0	4.15	4.21	3.77	2.52	1.24	2.08	45.0	4.34	4.54	4.48	2.71
47.5	4.41	4.45	4.12	3.19	2.03	2.30	47.5	4.59	4.74	4.67	3.44
50.0	4.63	4.65	4.42	3.78	2.77	2.59	50.0	4.79	4.89	4.82	4.07
52.5	4.80	4.81	4.67	4.29	3.46	2.95	52.5	4.94	5.00	4.93	4.61
55.0	4.92	4.92	4.87	4.73	4.08	3.37	55.0	5.03	5.06	4.99	5.05
57.5	4.99	4.98	5.02	5.10	4.63	3.82	57.5	5.08	5.06	5.00	5.39
60.0	5.01	4.99	5.12	5.38	5.10	4.28	60.0	5.07	5.01	4.95	5.65
62.5	4.98	4.94	5.15	5.58	5.48	4.71	62.5	4.99	4.89	4.85	5.80
65.0	4.87	4.83	5.11	5.69	5.75	5.08	65.0	4.85	4.71	4.68	5.85
67.5	4.69	4.64	4.98	5.70	5.92	5.35	67.5	4.62	4.43	4.42	5.79
70.0	4.42	4.35	4.76	5.60	5.95	5.51	70.0	4.28	4.06	4.06	5.60
72.5	4.03	3.95	4.42	5.35	5.83	5.51	72.5	3.82	3.56	3.57	5.25
75.0	3.49	3.40	3.91	4.93	5.52	5.32	75.0	3.20	2.89	2.92	4.71
77.5	2.74	2.63	3.19	4.28	4.96	4.86	77.5	2.35	1.99	2.03	3.93
80.0	1.68	1.56	2.14	3.29	4.05	4.04	80.0	1.16	0.76	0.81	2.78
82.5	0.12	-0.02	0.59	1.78	2.60	2.65	82.5	-0.55	-1.00	-0.95	1.08
85.0	-2.39	-2.56	-1.93	-0.71	0.15	0.26	85.0	-3.25	-3.75	-3.71	-1.63
87.5	-7.31	-7.50	-6.86	-5.62	-4.74	-4.60	87.5	-8.41	-8.97	-8.92	-6.82
90.0	-89.83	-90.28	-90.13	-89.81	-89.93	-91.38	90.0	-89.74	-89.98	-90.33	-89.60

Table A-16. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Six Frequencies and Five Soil Conditions, for 5.4 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials (Concluded)

THETA	[Elevation Angle $\psi = 90^\circ - \theta$]									
	Very Dry Ground $\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$									
	5 MHz	10 MHz	15 MHz	20 MHz	25 MHz	30 MHz	30 MHz	30 MHz	30 MHz	30 MHz
0.0	-88.55	-90.69	-90.68	-89.97	-89.86	-91.48				
2.5	-18.93	-17.96	-17.30	-25.36	-17.11	-17.56				
5.0	-12.92	-11.96	-11.32	-19.68	-11.28	-11.60				
7.5	-9.43	-8.48	-7.87	-16.74	-8.06	-8.19				
10.0	-6.96	-6.03	-5.47	-15.08	-5.99	-5.84				
12.5	-5.06	-4.17	-3.66	-14.26	-4.60	-4.09				
15.0	-3.53	-2.67	-2.23	-14.08	-3.68	-2.71				
17.5	-2.25	-1.43	-1.06	-14.39	-3.10	-1.61				
20.0	-1.17	-0.38	-0.09	-14.78	-2.79	-0.72				
22.5	-0.23	0.51	0.73	-14.44	-2.67	0.01				
25.0	0.60	1.28	1.42	-12.74	-2.66	0.60				
27.5	1.32	1.95	2.01	-10.21	-2.68	1.07				
30.0	1.95	2.53	2.52	-7.65	-2.61	1.42				
32.5	2.52	3.03	2.96	-5.34	-2.37	1.69				
35.0	3.02	3.47	3.35	-3.34	-1.90	1.88				
37.5	3.45	3.85	3.68	-1.62	-1.21	2.01				
40.0	3.84	4.17	3.98	-0.15	-0.38	2.11				
42.5	4.17	4.44	4.23	1.10	0.52	2.21				
45.0	4.45	4.66	4.44	2.18	1.42	2.35				
47.5	4.68	4.83	4.62	3.10	2.29	2.56				
50.0	4.86	4.95	4.76	3.88	3.08	2.84				
52.5	5.00	5.03	4.86	4.52	3.79	3.20				
55.0	5.08	5.05	4.93	5.05	4.41	3.61				
57.5	5.11	5.03	4.94	5.46	4.94	4.05				
60.0	5.08	4.95	4.91	5.76	5.36	4.48				
62.5	4.98	4.81	4.81	5.96	5.68	4.87				
65.0	4.81	4.59	4.65	6.04	5.88	5.17				
67.5	4.55	4.30	4.40	6.00	5.95	5.37				
70.0	4.19	3.90	4.05	5.82	5.89	5.44				
72.5	3.70	3.37	3.57	5.48	5.65	5.33				
75.0	3.04	2.69	2.92	4.95	5.21	5.01				
77.5	2.14	1.77	2.04	4.17	4.51	4.41				
80.0	0.91	0.52	0.82	3.03	3.43	3.42				
82.5	-0.85	-1.26	-0.94	1.33	1.78	1.84				
85.0	-3.61	-4.03	-3.69	-1.39	-0.89	-0.79				
87.5	-8.83	-9.26	-8.91	-6.58	-6.06	-5.93				
90.0	-88.55	-90.69	-90.68	-89.97	-89.86	-91.48				

SECTION A3

6.3 METER MONOPOLE CONFIGURATION RESULTS




Figure A-60. Antenna Input Impedance (Resistance and Reactance) versus Frequency in Wet Ground for 6.3 Mc. *er* High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-61. Antenna Input Impedance (Resistance and Reactance) versus Frequency in Moist Clay for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-62. Antenna Input Impedance (Resistance and Reactance) versus Frequency in Medium Dry Ground for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-63. Antenna Input Impedance (Resistance and Reactance) versus Frequency in Sand for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-64. Antenna Input Impedance (Resistance and Reactance) versus Frequency in Very Dry Ground for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-65. Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-66. Cable Mismatch Loss versus Frequency and Five Soil Conditions for 75 ohm Coaxial Cable Feeding 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

Table A-17. Antenna Input Resistance (ohms), Reactance (ohms), Magnitude Squared of Reflection Coefficient ($|\Gamma|^2$), and Mismatch Loss (dB) versus Frequency for Five Soil Conditions for 6.3 Meter High Monopole and 12 Meter Radius Ground Screen of 16 Radials and a 75 ohm Feed Cable
(Supports Vol. 1, Table 12)

Freq	R	X	$ \Gamma ^2$	MML (dB)	
5.0	6.92	-172.89	9.43279E-01	12.46	Wet Ground $\epsilon_r = 30, \sigma = 15 \text{ mS/m}$
7.5	17.53	-79.74	6.47576E-01	4.53	
10.0	36.65	-16.76	1.37452E-01	0.64	
12.5	75.25	31.55	4.22240E-02	0.19	
15.0	149.16	54.33	1.58850E-01	0.75	
17.5	237.06	-10.45	2.70509E-01	1.37	
20.0	206.71	-127.21	3.50947E-01	1.88	
22.5	118.69	-150.02	4.06758E-01	2.27	
25.0	65.97	-122.78	4.33678E-01	2.47	
27.5	42.88	-87.91	4.05114E-01	2.26	
30.0	38.10	-55.10	2.77810E-01	1.41	
5.0	6.63	-172.69	9.45454E-01	12.63	Moist Clay $\epsilon_r = 10, \sigma = 15 \text{ mS/m}$
7.5	17.05	-79.41	6.53930E-01	4.61	
10.0	36.61	-15.39	1.34749E-01	0.63	
12.5	76.56	32.69	4.45537E-02	0.20	
15.0	150.32	53.25	1.58732E-01	0.75	
17.5	234.92	-10.82	2.67152E-01	1.35	
20.0	206.01	-124.88	3.46426E-01	1.85	
22.5	119.46	-148.51	4.01414E-01	2.23	
25.0	66.36	-122.15	4.29614E-01	2.44	
27.5	42.49	-87.04	4.03754E-01	2.25	
30.0	37.59	-53.31	2.73339E-01	1.39	
5.0	7.32	-170.16	9.38583E-01	12.12	Medium Dry Ground $\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$
7.5	20.47	-78.25	5.96928E-01	3.95	
10.0	39.84	-16.60	1.12305E-01	0.52	
12.5	77.74	29.43	3.61164E-02	0.16	
15.0	146.94	52.57	1.52604E-01	0.72	
17.5	238.04	-6.57	2.71588E-01	1.38	
20.0	208.52	-125.39	3.49090E-01	1.86	
22.5	122.11	-150.37	4.03981E-01	2.25	
25.0	66.69	-123.39	4.33273E-01	2.47	
27.5	43.22	-87.13	3.98831E-01	2.21	
30.0	39.07	-53.49	2.61620E-01	1.32	
5.0	6.06	-170.45	9.48993E-01	12.92	Sandy Soil $\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$
7.5	19.42	-74.15	5.95821E-01	3.93	
10.0	44.60	-12.81	7.52202E-02	0.34	
12.5	79.59	24.55	2.54591E-02	0.11	
15.0	139.99	55.74	1.48610E-01	0.70	
17.5	242.38	0.61	2.78125E-01	1.42	
20.0	211.20	-122.75	3.46656E-01	1.85	
22.5	127.47	-148.26	3.92769E-01	2.17	
25.0	69.91	-124.82	4.26671E-01	2.42	
27.5	44.07	-87.06	3.92344E-01	2.16	
30.0	40.17	-52.06	2.45597E-01	1.22	
5.0	4.36	-171.01	9.63191E-01	14.34	Very Dry Ground $\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$
7.5	20.82	-64.70	5.32818E-01	3.31	
10.0	53.49	-21.92	5.55211E-02	0.25	
12.5	69.53	15.05	1.21466E-02	0.05	
15.0	147.79	80.64	2.10215E-01	1.02	
17.5	250.99	-18.09	2.93623E-01	1.51	
20.0	199.32	-112.90	3.20483E-01	1.68	
22.5	132.91	-155.00	4.07110E-01	2.27	
25.0	67.02	-127.27	4.47141E-01	2.57	
27.5	44.67	-85.92	3.82508E-01	2.09	
30.0	40.71	-53.19	2.46922E-01	1.23	




Figure A-67. Antenna Noise (Ohmic Loss) versus Frequency and Five Soil Conditions for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 32 Radials

1A094A-2

Table A-18. 6.3 Meter High Monopole Antenna: Efficiency and Noise Figure versus Frequency for Five Soil Conditions for 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178 Deep

(Supports Vol. 1, Table 12)

Frequency (MHz)	Soil Characteristics									
	Very Good (Wet Ground)		Good (Moist Clay)		Average (Medium Dry Ground)		Fair (Sand)		Poor (Very Dry Ground)	
	$\epsilon_r = 30, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$		$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$	
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)
5.0	9.7	5.2	10.0	5.1	6.2	7.1	5.3	7.8	6.8	6.7
7.5	10.3	4.9	10.0	5.1	7.1	6.5	6.0	7.3	9.1	5.4
10.0	10.4	4.9	9.5	5.3	7.7	6.2	7.3	6.4	8.3	5.9
12.5	10.7	4.8	9.3	5.4	8.1	5.9	7.8	6.1	9.2	5.4
15.0	10.8	4.7	9.0	5.5	8.4	5.8	7.4	6.4	7.0	6.6
17.5	10.9	4.7	8.6	5.7	8.6	5.7	7.3	6.4	7.5	6.3
20.0	11.2	4.6	8.5	5.8	9.2	5.4	8.0	6.0	8.5	5.8
22.5	11.7	4.4	8.9	5.5	10.2	5.0	9.3	5.3	9.6	5.2
25.0	12.7	4.0	10.5	4.9	12.4	4.1	12.1	4.2	12.8	4.0
27.5	14.8	3.3	14.0	3.6	15.9	3.0	16.8	2.8	17.0	2.7
30.0	17.4	2.7	18.5	2.4	19.0	2.3	20.8	2.0	21.0	2.0




Figure A-68. System Internal Noise Figure Cumulative Contributions for Case of Wet Ground and Maximum Length Cable for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-69. System Internal Noise Figure Cumulative Contributions for Case of Moist Clay and Maximum Length Cable for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-70. System Internal Noise Figure Cumulative Contributions for Case of Medium Dry Ground and Maximum Length Cable for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-71. System Internal Noise Figure Cumulative Contributions for Case of Sandy Soil and Maximum Length Cable for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-72. System Internal Noise Figure Cumulative Contributions for Case of Very Dry Ground and Maximum Length Cable for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-73. System Internal Noise Figures versus Frequency, Soil Condition, and Maximum and Minimum Cable Lengths for 6.3 Meter High Monopole Antenna with 12 Meter Radius Ground Screen of 16 Radial Wires




Figure A-74. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 5 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-75. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 10 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-76. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 15 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-77. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 20 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-78. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 25 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-79. Antenna Directivity versus Elevation Angle and Five Soil Conditions, at Frequency of 30 MHz, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials




Figure A-80. Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole Antenna with 12 Meter Radius Ground Screen of 16 Radials, for a Wet Ground Condition




Figure A-81. Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole Antenna with 12 Meter Radius Ground Screen of 16 Radials, for a Moist Clay Condition




Figure A-82. Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole Antenna with 12 Meter Radius Ground Screen of 16 Radials, for a Medium Dry Ground Condition




Figure A-83. Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole Antenna with 16 Radials, for a Sandy Soil Condition

Very Dry Ground $\epsilon=4$ $\sigma=0.15$

16 radials

- o = 5 MHz
- Δ = 10 MHz
- + = 15 MHz
- x = 20 MHz
- = 25 MHz
- ▽ = 30 MHz

Conductivity σ , in mS/m




Figure A-84. Antenna Directivity versus Elevation Angle and Frequency, for 6.3 Meter High Monopole Antenna with 12 Meter Radius Ground Screen of 16 Radials, for a Very Dry Ground Condition

Table A-19. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Eleven Frequencies and Five Soil Conditions, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radiats

(Elevation Angle $\psi = 90^\circ - \theta$)

Wet Ground

$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$

Directivity in dBi

θ	F = 5 MHz	7.5 MHz	10	12.5	15	17.5	20	22.5	25	27.5	30
0.0	-86.87	-87.13	-87.15	-87.27	-87.33	-87.38	-87.47	-87.66	-88.04	-88.70	-89.39
2.5	-20.62	-20.73	-21.10	-21.86	-23.27	-25.55	-27.65	-25.38	-21.10	-18.03	-16.64
5.0	-14.61	-14.72	-15.08	-15.84	-17.23	-19.48	-21.59	-19.40	-15.13	-12.04	-10.64
7.5	-11.10	-11.21	-11.57	-12.31	-13.68	-15.89	-18.00	-15.94	-11.70	-8.58	-7.15
10.0	-8.62	-8.72	-9.07	-9.80	-11.15	-13.30	-15.40	-13.52	-9.32	-6.17	-4.69
12.5	-6.71	-6.81	-7.15	-7.86	-9.16	-11.25	-13.34	-11.68	-7.53	-4.34	-2.82
15.0	-5.16	-5.25	-5.58	-6.27	-7.52	-9.53	-11.59	-10.21	-6.14	-2.90	-1.32
17.5	-3.86	-3.94	-4.26	-4.92	-6.12	-8.04	-10.07	-8.98	-5.02	-1.73	-0.09
20.0	-2.75	-2.82	-3.12	-3.75	-4.89	-6.71	-8.69	-7.92	-4.11	-0.78	0.94
22.5	-1.78	-1.84	-2.12	-2.72	-3.80	-5.50	-7.42	-6.98	-3.37	0.01	1.80
25.0	-0.92	-0.98	-1.24	-1.80	-2.81	-4.40	-6.24	-6.11	-2.76	0.64	2.52
27.5	-0.16	-0.20	-0.44	-0.97	-1.91	-3.37	-5.12	-5.29	-2.26	1.15	3.12
30.0	0.52	0.49	0.27	-0.21	-1.08	-2.42	-4.06	-4.50	-1.85	1.55	3.60
32.5	1.13	1.11	0.91	0.48	-0.31	-1.52	-3.04	-3.70	-1.49	1.84	3.97
35.0	1.68	1.67	1.50	1.11	0.40	-0.69	-2.08	-2.89	-1.16	2.04	4.24
37.5	2.18	2.18	2.03	1.69	1.06	0.10	-1.16	-2.08	-0.84	2.17	4.41
40.0	2.63	2.64	2.52	2.22	1.67	0.83	-0.29	-1.25	-0.50	2.22	4.49
42.5	3.03	3.06	2.96	2.70	2.24	1.52	0.54	-0.42	-0.11	2.23	4.47
45.0	3.39	3.43	3.35	3.14	2.76	2.16	1.32	0.41	0.35	2.22	4.37
47.5	3.71	3.76	3.71	3.54	3.23	2.75	2.05	1.21	0.88	2.21	4.19
50.0	3.99	4.05	4.02	3.90	3.67	3.30	2.73	1.99	1.48	2.25	3.95
52.5	4.24	4.30	4.30	4.22	4.06	3.79	3.36	2.73	2.12	2.37	3.68
55.0	4.45	4.52	4.53	4.49	4.40	4.23	3.92	3.42	2.79	2.60	3.40
57.5	4.62	4.69	4.72	4.72	4.69	4.62	4.43	4.06	3.46	2.93	3.18
60.0	4.74	4.82	4.86	4.90	4.93	4.95	4.87	4.62	4.10	3.36	3.04
62.5	4.83	4.90	4.96	5.03	5.12	5.21	5.24	5.11	4.68	3.84	3.03
65.0	4.87	4.93	5.00	5.10	5.24	5.40	5.52	5.51	5.19	4.33	3.15
67.5	4.85	4.90	4.97	5.10	5.29	5.52	5.72	5.82	5.61	4.78	3.36
70.0	4.77	4.80	4.88	5.02	5.25	5.54	5.82	6.01	5.91	5.14	3.60
72.5	4.60	4.61	4.68	4.84	5.10	5.45	5.79	6.07	6.07	5.38	3.80
75.0	4.33	4.30	4.36	4.54	4.82	5.21	5.61	5.96	6.05	5.45	3.88
77.5	3.90	3.82	3.87	4.05	4.36	4.78	5.23	5.64	5.81	5.28	3.76
80.0	3.24	3.10	3.12	3.30	3.62	4.06	4.55	5.01	5.24	4.78	3.31
82.5	2.18	1.95	1.94	2.10	2.42	2.88	3.40	3.90	4.17	3.77	2.35
85.0	0.31	-0.03	-0.10	0.04	0.36	0.82	1.35	1.87	2.18	1.82	0.43
87.5	-3.77	-4.26	-4.40	-4.30	-3.99	-3.53	-3.00	-2.47	-2.14	-2.48	-3.85
90.0	-86.87	-87.13	-87.15	-87.27	-87.33	-87.38	-87.47	-87.66	-88.04	-88.70	-89.39

Table A-19. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Eleven Frequencies and Five Soil Conditions, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Continued)

(Elevation Angle $\psi = 90^\circ - \theta$)

Moist Clay											
$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$											
Directivity in dBi											
	F = 5 MHz	7.5 MHz	10	12.5	15	17.5	20	22.5	25	27.5	30
0.0	-86.97	-86.98	-86.75	-86.66	-86.52	-86.36	-86.29	-86.49	-87.19	-88.46	-89.66
2.5	-20.61	-20.67	-20.90	-21.42	-22.56	-24.84	-27.35	-24.09	-19.59	-17.19	-16.64
5.0	-14.60	-14.65	-14.88	-15.39	-16.53	-18.79	-21.28	-18.10	-13.62	-11.21	-10.63
7.5	-11.09	-11.14	-11.37	-11.87	-12.99	-15.20	-17.67	-14.65	-10.19	-7.75	-7.15
10.0	-8.61	-8.66	-8.88	-9.37	-10.47	-12.62	-15.04	-12.23	-7.82	-5.35	-4.69
12.5	-6.70	-6.74	-6.95	-7.43	-8.50	-10.57	-12.95	-10.40	-6.04	-3.53	-2.82
15.0	-5.15	-5.19	-5.39	-5.85	-6.87	-8.87	-11.17	-8.93	-4.65	-2.10	-1.32
17.5	-3.85	-3.88	-4.07	-4.51	-5.49	-7.39	-9.61	-7.70	-3.54	-0.94	-0.09
20.0	-2.73	-2.76	-2.93	-3.35	-4.29	-6.07	-8.21	-6.65	-2.63	0.01	0.95
22.5	-1.76	-1.78	-1.94	-2.33	-3.22	-4.88	-6.91	-5.73	-1.89	0.80	1.81
25.0	-0.91	-0.91	-1.06	-1.43	-2.25	-3.80	-5.70	-4.88	-1.28	1.44	2.55
27.5	-0.15	-0.14	-0.27	-0.61	-1.38	-2.80	-4.57	-4.09	-0.77	1.96	3.16
30.0	0.53	0.55	0.44	0.13	-0.57	-1.86	-3.50	-3.33	-0.35	2.38	3.66
32.5	1.14	1.17	1.08	0.80	0.16	-1.00	-2.49	-2.58	0.01	2.70	4.06
35.0	1.69	1.74	1.66	1.42	0.85	-0.18	-1.53	-1.83	0.33	2.94	4.37
37.5	2.19	2.24	2.19	1.98	1.47	0.57	-0.62	-1.07	0.64	3.11	4.59
40.0	2.64	2.70	2.67	2.49	2.06	1.28	0.24	-0.32	0.94	3.21	4.72
42.5	3.04	3.12	3.10	2.96	2.59	1.94	1.04	0.44	1.27	3.27	4.78
45.0	3.41	3.49	3.49	3.38	3.08	2.55	1.80	1.18	1.63	3.30	4.76
47.5	3.73	3.82	3.84	3.76	3.53	3.11	2.50	1.91	2.03	3.32	4.67
50.0	4.01	4.11	4.14	4.10	3.93	3.62	3.14	2.61	2.48	3.35	4.53
52.5	4.26	4.36	4.40	4.39	4.28	4.07	3.73	3.27	2.96	3.41	4.35
55.0	4.47	4.56	4.63	4.64	4.59	4.48	4.25	3.88	3.46	3.52	4.15
57.5	4.64	4.73	4.80	4.84	4.85	4.83	4.71	4.43	3.96	3.69	3.95
60.0	4.77	4.86	4.93	5.00	5.05	5.11	5.10	4.92	4.44	3.90	3.78
62.5	4.85	4.93	5.01	5.09	5.19	5.33	5.42	5.32	4.88	4.15	3.66
65.0	4.89	4.95	5.03	5.13	5.27	5.47	5.65	5.64	5.24	4.40	3.57
67.5	4.87	4.91	4.98	5.09	5.26	5.52	5.78	5.86	5.52	4.61	3.52
70.0	4.78	4.79	4.85	4.97	5.16	5.47	5.79	5.95	5.68	4.75	3.47
72.5	4.61	4.58	4.62	4.73	4.95	5.30	5.68	5.90	5.69	4.78	3.36
75.0	4.33	4.25	4.26	4.36	4.58	4.96	5.38	5.67	5.52	4.63	3.13
77.5	3.89	3.74	3.70	3.78	4.01	4.41	4.86	5.19	5.10	4.23	2.70
80.0	3.21	2.96	2.87	2.92	3.13	3.54	4.02	4.38	4.32	3.49	1.93
82.5	2.11	1.74	1.57	1.57	1.76	2.16	2.65	3.03	3.00	2.19	0.63
85.0	0.17	-0.37	-0.64	-0.71	-0.55	-0.17	0.31	0.70	0.68	-0.11	-1.68
87.5	-4.03	-4.81	-5.21	-5.36	-5.25	-4.90	-4.44	-4.06	-4.08	-4.88	-6.45
90.0	-86.97	-86.98	-86.75	-86.66	-86.52	-86.36	-86.29	-86.49	-87.19	-88.46	-89.66

Table A-19. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Eleven Frequencies and Five Soil Conditions, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Continued)

(Elevation Angle $\psi = 90^\circ - \theta$)												
Medium Dry Ground												
$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$												
θ	Directivity in dBi											
	F = 5 MHz	7.5 MHz	10	12.5	15	17.5	20	22.5	25	27.5	30	
0.0	-84.93	-85.53	-85.87	-86.10	-86.21	-86.32	-86.61	-87.09	-87.92	-89.01	-89.78	
2.5	-19.44	-19.52	-19.89	-20.63	-22.33	-26.03	-27.11	-22.99	-20.19	-18.15	-17.05	
5.0	-13.44	-13.51	-13.88	-14.61	-16.29	-19.94	-21.05	-17.02	-14.22	-12.17	-11.06	
7.5	-9.93	-10.01	-10.37	-11.09	-12.75	-16.30	-17.47	-13.59	-10.78	-8.70	-7.58	
10.0	-7.46	-7.53	-7.89	-8.60	-10.22	-13.64	-14.89	-11.22	-8.40	-6.29	-5.14	
12.5	-5.56	-5.63	-5.98	-6.67	-8.24	-11.51	-12.83	-9.43	-6.61	-4.46	-3.28	
15.0	-4.02	-4.09	-4.43	-5.10	-6.61	-9.70	-11.09	-8.01	-5.21	-3.01	-1.80	
17.5	-2.74	-2.80	-3.13	-3.78	-5.22	-8.11	-9.55	-6.85	-4.08	-1.83	-0.58	
20.0	-1.64	-1.70	-2.02	-2.63	-4.00	-6.68	-8.16	-5.86	-3.16	-0.86	0.44	
22.5	-0.69	-0.75	-1.05	-1.63	-2.92	-5.38	-6.86	-5.01	-2.40	-0.05	1.29	
25.0	0.14	0.09	-0.19	-0.75	-1.94	-4.19	-5.64	-4.23	-1.76	0.61	2.00	
27.5	0.87	0.82	0.56	0.05	-1.06	-3.08	-4.49	-3.50	-1.22	1.15	2.59	
30.0	1.53	1.48	1.24	0.76	-0.25	-2.05	-3.39	-2.80	-0.76	1.60	3.08	
32.5	2.11	2.06	1.84	1.41	0.50	-1.10	-2.35	-2.10	-0.35	1.95	3.47	
35.0	2.62	2.59	2.39	1.99	1.18	-0.21	-1.36	-1.39	0.02	2.22	3.77	
37.5	3.08	3.05	2.87	2.52	1.81	0.61	-0.42	-0.68	0.39	2.44	3.99	
40.0	3.48	3.46	3.30	3.00	2.39	1.38	0.46	0.05	0.77	2.60	4.13	
42.5	3.84	3.82	3.69	3.43	2.92	2.08	1.29	0.78	1.18	2.74	4.20	
45.0	4.15	4.13	4.02	3.81	3.40	2.72	2.05	1.50	1.62	2.86	4.21	
47.5	4.41	4.40	4.32	4.15	3.83	3.31	2.76	2.20	2.10	2.99	4.17	
50.0	4.62	4.62	4.56	4.44	4.21	3.83	3.40	2.88	2.61	3.15	4.10	
52.5	4.80	4.80	4.76	4.68	4.54	4.29	3.97	3.51	3.14	3.35	4.01	
55.0	4.92	4.92	4.91	4.88	4.82	4.69	4.48	4.09	3.67	3.59	3.94	
57.5	4.99	5.00	5.01	5.02	5.04	5.03	4.91	4.61	4.19	3.88	3.90	
60.0	5.02	5.03	5.06	5.11	5.20	5.29	5.27	5.05	4.66	4.19	3.90	
62.5	4.98	5.00	5.05	5.13	5.29	5.48	5.55	5.42	5.08	4.50	3.94	
65.0	4.88	4.90	4.97	5.09	5.31	5.58	5.73	5.69	5.41	4.79	4.01	
67.5	4.70	4.72	4.80	4.96	5.24	5.58	5.81	5.85	5.65	5.01	4.08	
70.0	4.43	4.45	4.55	4.73	5.06	5.47	5.76	5.89	5.76	5.13	4.12	
72.5	4.04	4.06	4.17	4.38	4.76	5.23	5.58	5.77	5.71	5.12	4.06	
75.0	3.50	3.51	3.64	3.87	4.29	4.81	5.21	5.47	5.47	4.92	3.84	
77.5	2.75	2.76	2.89	3.15	3.59	4.16	4.60	4.92	4.98	4.46	3.39	
80.0	1.70	1.69	1.83	2.10	2.58	3.18	3.66	4.01	4.12	3.65	2.59	
82.5	0.13	0.12	0.27	0.55	1.04	1.67	2.17	2.57	2.72	2.27	1.24	
85.0	-2.38	-2.40	-2.26	-1.97	-1.46	-0.82	-0.29	0.13	0.30	-0.11	-1.13	
87.5	-7.30	-7.34	-7.19	-6.90	-6.39	-5.73	-5.19	-4.76	-4.57	-4.97	-5.98	
90.0	-84.93	-85.53	-85.87	-86.10	-86.21	-86.32	-86.61	-87.09	-87.92	-89.01	-89.78	

Table A-19. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Eleven Frequencies and Five Soil Conditions, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Continued)

(Elevation Angle $\psi = 90^\circ - \theta$)

Sandy Soil

$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$

θ	Directivity in dBi										
	F = 5 MHz	7.5 MHz	10	12.5	15	17.5	20	22.5	25	27.5	30
0.0	-84.24	-84.77	-85.62	-85.92	-85.67	-85.60	-86.01	-86.70	-87.82	-89.25	-90.17
2.5	-19.20	-19.05	-18.78	-18.89	-20.74	-27.15	-28.85	-20.99	-18.13	-17.59	-17.90
5.0	-13.19	-13.04	-12.77	-12.88	-14.72	-21.02	-22.83	-15.06	-12.19	-11.61	-11.88
7.5	-9.69	-9.55	-9.28	-9.39	-11.21	-17.34	-19.30	-11.68	-8.80	-8.16	-8.36
10.0	-7.22	-7.08	-6.82	-6.93	-8.72	-14.61	-16.75	-9.39	-6.48	-5.76	-5.88
12.5	-5.32	-5.18	-4.93	-5.05	-6.80	-12.39	-14.70	-7.70	-4.77	-3.95	-3.96
15.0	-3.78	-3.65	-3.41	-3.53	-5.23	-10.49	-12.91	-6.39	-3.46	-2.53	-2.42
17.5	-2.50	-2.37	-2.14	-2.26	-3.91	-8.79	-11.26	-5.36	-2.43	-1.37	-1.14
20.0	-1.40	-1.28	-1.06	-1.19	-2.77	-7.25	-9.69	-4.52	-1.62	-0.43	-0.05
22.5	-0.45	-0.33	-0.13	-0.26	-1.76	-5.83	-8.18	-3.79	-0.96	0.35	0.86
25.0	0.38	0.49	0.67	0.55	-0.87	-4.52	-6.71	-3.15	-0.44	1.00	1.64
27.5	1.11	1.22	1.38	1.26	-0.06	-3.30	-5.30	-2.54	-0.01	1.53	2.30
30.0	1.76	1.86	2.01	1.89	0.67	-2.16	-3.96	-1.94	0.35	1.97	2.85
32.5	2.33	2.43	2.56	2.44	1.33	-1.12	-2.69	-1.31	0.67	2.33	3.30
35.0	2.84	2.93	3.05	2.93	1.94	-0.14	-1.51	-0.67	0.97	2.61	3.66
37.5	3.29	3.38	3.48	3.37	2.50	0.75	-0.42	0.01	1.26	2.84	3.94
40.0	3.69	3.77	3.85	3.75	3.00	1.57	0.59	0.70	1.58	3.03	4.15
42.5	4.04	4.10	4.17	4.08	3.46	2.31	1.51	1.40	1.93	3.20	4.29
45.0	4.33	4.39	4.44	4.37	3.87	2.99	2.34	2.09	2.32	3.35	4.37
47.5	4.58	4.63	4.67	4.61	4.23	3.59	3.09	2.76	2.74	3.50	4.41
50.0	4.78	4.83	4.84	4.80	4.54	4.12	3.75	3.38	3.19	3.67	4.42
52.5	4.93	4.97	4.97	4.95	4.80	4.58	4.32	3.96	3.64	3.86	4.41
55.0	5.03	5.06	5.05	5.04	5.01	4.96	4.82	4.48	4.09	4.07	4.39
57.5	5.08	5.10	5.08	5.09	5.16	5.27	5.22	4.92	4.51	4.30	4.38
60.0	5.07	5.08	5.05	5.07	5.25	5.49	5.53	5.29	4.88	4.52	4.37
62.5	5.00	4.99	4.95	4.99	5.27	5.63	5.75	5.56	5.19	4.72	4.36
65.0	4.85	4.83	4.78	4.84	5.20	5.68	5.87	5.74	5.41	4.87	4.33
67.5	4.62	4.59	4.53	4.60	5.04	5.61	5.87	5.80	5.52	4.95	4.27
70.0	4.29	4.24	4.17	4.26	4.77	5.42	5.74	5.73	5.50	4.93	4.14
72.5	3.83	3.76	3.68	3.79	4.36	5.08	5.45	5.49	5.33	4.75	3.90
75.0	3.21	3.12	3.02	3.14	3.77	4.56	4.96	5.05	4.94	4.38	3.49
77.5	2.36	2.24	2.14	2.27	2.94	3.78	4.22	4.35	4.29	3.75	2.83
80.0	1.18	1.03	0.92	1.05	1.76	2.64	3.11	3.28	3.26	2.74	1.81
82.5	-0.53	-0.71	-0.84	-0.70	0.03	0.94	1.44	1.64	1.65	1.15	0.22
85.0	-3.23	-3.45	-3.59	-3.45	-2.70	-1.76	-1.26	-1.04	-1.00	-1.48	-2.41
87.5	-8.39	-8.64	-8.80	-8.66	-7.90	-6.95	-6.44	-6.20	-6.15	-6.62	-7.55
90.0	-84.24	-84.77	-85.62	-85.92	-85.67	-85.60	-86.01	-86.70	-87.82	-89.25	-90.17

Table A-19. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Eleven Frequencies and Five Soil Conditions, for 6.3 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Concluded)

(Elevation Angle $\psi = 90^\circ - \theta$)												
Very Dry Ground												
$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$												
Directivity in dBi												
θ	F = 5 MHz	7.5 MHz	10	12.5	15	17.5	20	22.5	25	27.5	30	
0.0	-85.32	-86.59	-86.15	-86.62	-85.41	-85.72	-86.27	-86.81	-88.05	-89.31	-90.22	
2.5	-18.96	-18.37	-18.21	-18.15	-22.94	-34.78	-23.13	-19.18	-17.97	-20.02	-19.03	
5.0	-12.96	-12.36	-12.21	-12.15	-16.93	-28.30	-17.25	-13.25	-12.03	-13.97	-12.97	
7.5	-9.46	-8.87	-8.72	-8.67	-13.42	-24.08	-13.97	-9.89	-8.64	-10.40	-9.40	
10.0	-6.99	-6.42	-6.27	-6.24	-10.94	-20.70	-11.79	-7.61	-6.33	-7.84	-6.83	
12.5	-5.09	-4.54	-4.40	-4.37	-9.01	-17.78	-10.23	-5.94	-4.62	-5.84	-4.82	
15.0	-3.56	-3.03	-2.89	-2.88	-7.42	-15.17	-9.07	-4.68	-3.31	-4.20	-3.18	
17.5	-2.28	-1.77	-1.65	-1.65	-6.06	-12.81	-8.16	-3.70	-2.29	-2.82	-1.79	
20.0	-1.19	-0.71	-0.59	-0.61	-4.86	-10.65	-7.37	-2.93	-1.48	-1.65	-0.60	
22.5	-0.25	0.21	0.31	0.27	-3.78	-8.68	-6.62	-2.31	-0.83	-0.64	0.41	
25.0	0.57	1.00	1.09	1.04	-2.78	-6.89	-5.82	-1.79	-0.32	0.22	1.28	
27.5	1.29	1.69	1.77	1.71	-1.85	-5.26	-4.93	-1.34	0.10	0.95	2.02	
30.0	1.93	2.30	2.37	2.29	-0.97	-3.77	-3.95	-0.92	0.44	1.56	2.64	
32.5	2.50	2.82	2.89	2.80	-0.15	-2.41	-2.90	-0.50	0.74	2.07	3.16	
35.0	3.00	3.29	3.34	3.24	0.63	-1.18	-1.82	-0.06	1.00	2.48	3.57	
37.5	3.44	3.69	3.73	3.63	1.37	-0.07	-0.75	0.42	1.27	2.81	3.88	
40.0	3.82	4.04	4.07	3.96	2.05	0.93	0.28	0.95	1.55	3.07	4.12	
42.5	4.16	4.33	4.35	4.25	2.68	1.84	1.24	1.51	1.87	3.28	4.28	
45.0	4.44	4.58	4.59	4.49	3.26	2.64	2.12	2.09	2.23	3.45	4.38	
47.5	4.67	4.77	4.78	4.69	3.78	3.35	2.92	2.68	2.63	3.62	4.43	
50.0	4.86	4.92	4.92	4.85	4.24	3.98	3.63	3.27	3.07	3.78	4.44	
52.5	4.99	5.02	5.02	4.95	4.64	4.51	4.25	3.82	3.53	3.95	4.43	
55.0	5.08	5.07	5.06	5.02	4.97	4.96	4.77	4.33	3.99	4.15	4.42	
57.5	5.11	5.07	5.05	5.03	5.24	5.32	5.21	4.78	4.43	4.36	4.40	
60.0	5.08	5.01	4.99	4.99	5.42	5.59	5.54	5.16	4.82	4.57	4.40	
62.5	4.99	4.88	4.86	4.88	5.53	5.76	5.78	5.45	5.15	4.76	4.40	
65.0	4.82	4.69	4.66	4.70	5.54	5.83	5.90	5.65	5.40	4.92	4.38	
67.5	4.56	4.40	4.38	4.44	5.45	5.79	5.91	5.73	5.54	5.00	4.33	
70.0	4.20	4.02	4.00	4.08	5.23	5.62	5.78	5.67	5.54	4.97	4.21	
72.5	3.71	3.51	3.49	3.59	4.87	5.30	5.50	5.45	5.38	4.80	3.98	
75.0	3.05	2.83	2.81	2.93	4.32	4.78	5.01	5.03	5.01	4.44	3.57	
77.5	2.16	1.92	1.90	2.04	3.52	4.01	4.27	4.34	4.37	3.81	2.92	
80.0	0.93	0.68	0.66	0.81	2.37	2.88	3.16	3.28	3.35	2.80	1.90	
82.5	-0.84	-1.09	-1.12	-0.95	0.66	1.18	1.48	1.64	1.75	1.22	0.31	
85.0	-3.60	-3.86	-3.88	-3.71	-2.06	-1.52	-1.21	-1.02	-0.90	-1.41	-2.32	
87.5	-8.82	-9.08	-9.11	-8.93	-7.25	-6.71	-6.39	-6.19	-6.05	-6.55	-7.46	
90.0	-85.32	-86.59	-86.15	-86.62	-85.41	-85.72	-86.27	-86.81	-88.05	-89.31	-90.22	

SECTION A4

6.0, 6.5, 7.0 METER MONOPOLE RESULTS

TA1788

Table A-20. Antenna Input Resistance and Reactance versus Frequency for Five Soil Conditions, for 6.0, 6.5 and 7.0 Meter High Monopoles with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep
(Supports Vol. 1, Table 12)

Frequency (MHz)	Soil Characteristics			
	Very Good	Good	Medium	Fair
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$ $\epsilon_r = 10, \sigma = 15 \text{ mS/m}$ $\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$ $\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$ $\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$			
Height = 6.0m				
5.0	6.26 - j182.6	5.99 - j182.1	6.65 - j179.3	5.36 - j179.8
17.5	210.3 + j19.8	209.3 + j18.7	210.4 + j22.3	212.6 + j28.5
30.0	38.6 - j71.4	38.0 - j70.1	39.1 - j70.2	40.0 - j69.3
Height = 6.5m				
5.0	7.32 - j167.3	7.04 - j167.5	7.70 - j164.8	6.44 - j165.0
17.5	247.9 - j37.1	245.4 - j36.7	250.2 - j32.7	256.4 - j25.5
30.0	40.0 - j44.3	39.7 - j42.3	41.3 - j42.6	42.6 - j41.0
Height = 7.0m				
5.0	8.44 - j153.1	8.41 - j152.5	8.83 - j149.7	7.42 - j151.2
17.5	241.2 - j110.1	239.4 - j107.6	246.9 - j106.9	257.3 - j103.4
30.0	53.4 - j19.4	53.8 - j17.3	55.5 - j18.1	57.2 - j16.4
				58.0 - j18.0

TA1780

Table A-21. Antenna Efficiency and Noise versus Frequency for Five Soil Conditions, for 6.0, 6.5 and 7.0 Meter High Monopoles with 12 Meter Radius Ground Screen of 16 Radials, 2 mm in Diameter and Buried 0.178m Deep
(Supports Vol. 1, Table 12)

Frequency (MHz)	Soil Characteristics														
	Very Good			Good			Medium			Fair			Poor		
	$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$			$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$			$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$			$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$			$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$		
	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	η (%)	NF (dB)	
Height = 6.0m															
5.0	30.1	5.2	30.9	5.1	19.3	7.1	16.8	7.7	21.2	6.7					
17.5	33.9	4.7	27.0	5.7	26.3	5.8	22.3	6.5	22.6	6.5					
30.0	50.0	3.0	50.7	2.9	54.9	2.6	59.6	2.2	61.1	2.1					
Height = 6.5m															
5.0	30.7	5.1	31.3	5.0	19.7	7.1	16.6	7.8	21.4	6.7					
17.5	34.4	4.6	27.0	5.7	27.1	5.6	23.0	6.4	23.8	6.2					
30.0	56.6	2.5	61.2	2.1	61.0	2.1	66.5	1.8	66.7	1.8					
Height = 7.0m															
5.0	30.4	5.0	31.9	5.0	20.2	7.0	16.9	7.7	21.7	6.6					
17.5	34.8	4.6	27.0	5.7	28.1	5.5	24.0	6.2	25.5	5.9					
30.0	60.2	2.2	64.3	1.9	60.8	2.2	64.5	1.9	64.2	1.9					




Figure A-85. Antenna Directivity versus Elevation Angle and Five Soil Conditions for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 5 MHz




Figure A-86. Antenna Directivity versus Elevation Angle and Five Soil Conditions for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 17.5 MHz




Figure A-87. Antenna Directivity versus Elevation Angle and Five Soil Conditions for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 30 MHz




Figure A-88. Antenna Directivity versus Elevation Angle and Frequency, for 6.5 Meter High Monopole with 16 Radials, for a Wet Ground Condition




Figure A-89. Antenna Directivity versus Elevation Angle and Frequency, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a Moist Clay Condition

Medium Dry Ground $\epsilon=10$ $\sigma=1.5$

16 radials
 o = 5 MHz
 Δ = 17.5 MHz
 + = 30 MHz

Conductivity σ , in mS/m




Figure A-90. Antenna Directivity versus Elevation Angle and Frequency, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a Medium Dry Ground Condition




Figure A-91. Antenna Directivity versus Elevation Angle and Frequency, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a Sandy Soil Condition




Figure A-92. Antenna Directivity versus Elevation Angle and Frequency, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials, for a Very Dry Ground Condition




Figure A-93. Antenna Directivity versus Elevation Angle and Five Soil Conditions for 6.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 30 MHz




Figure A-94. Antenna Directivity versus Elevation Angle and Five Soil Conditions for 7.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials at Frequency of 30 MHz

Table A-22. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$

WET GROUND			
THETA	5 MHz	17.5 MHz	30 MHz
0.0	-86.91	-87.40	-89.57
2.5	-20.63	-26.08	-16.45
5.0	-14.62	-20.01	-10.45
7.5	-11.11	-16.42	-6.95
10.0	-8.64	-13.81	-4.49
12.5	-6.72	-11.75	-2.60
15.0	-5.17	-10.01	-1.08
17.5	-3.87	-8.50	0.17
20.0	-2.76	-7.15	1.22
22.5	-1.79	-5.92	2.11
25.0	-0.93	-4.79	2.86
27.5	-0.17	-3.73	3.48
30.0	0.51	-2.75	4.00
32.5	1.12	-1.83	4.40
35.0	1.67	-0.96	4.71
37.5	2.17	-0.15	4.91
40.0	2.62	0.61	5.02
42.5	3.02	1.33	5.03
45.0	3.39	2.00	4.94
47.5	3.71	2.62	4.76
50.0	3.99	3.19	4.50
52.5	4.24	3.71	4.18
55.0	4.45	4.17	3.81
57.5	4.62	4.58	3.44
60.0	4.75	4.93	3.12
62.5	4.83	5.22	2.90
65.0	4.87	5.43	2.80
67.5	4.85	5.56	2.83
70.0	4.77	5.60	2.95
72.5	4.61	5.52	3.08
75.0	4.33	5.30	3.13
77.5	3.91	4.87	3.00
80.0	3.25	4.17	2.56
82.5	2.18	2.99	1.61
85.0	0.31	0.94	-0.29
87.5	-3.76	-3.42	-4.56
90.0	-86.91	-87.40	-89.57

$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$

MOIST CLAY			
THETA	5 MHz	17.5 MHz	30 MHz
0.0	-87.00	-86.35	-89.91
2.5	-20.63	-25.37	-16.66
5.0	-14.62	-19.31	-10.65
7.5	-11.11	-15.71	-7.16
10.0	-8.63	-13.12	-4.69
12.5	-6.72	-11.06	-2.80
15.0	-5.17	-9.33	-1.28
17.5	-3.87	-7.83	-0.03
20.0	-2.75	-6.50	1.03
22.5	-1.78	-5.28	1.93
25.0	-0.93	-4.17	2.69
27.5	-0.17	-3.14	3.33
30.0	0.52	-2.18	3.86
32.5	1.13	-1.28	4.29
35.0	1.68	-0.44	4.63
37.5	2.18	0.34	4.88
40.0	2.63	1.08	5.04
42.5	3.03	1.76	5.12
45.0	3.40	2.40	5.11
47.5	3.72	2.99	5.03
50.0	4.00	3.52	4.87
52.5	4.25	4.01	4.66
55.0	4.46	4.43	4.40
57.5	4.63	4.80	4.12
60.0	4.76	5.11	3.85
62.5	4.85	5.35	3.59
65.0	4.88	5.51	3.37
67.5	4.87	5.58	3.19
70.0	4.78	5.54	3.03
72.5	4.61	5.38	2.84
75.0	4.33	5.06	2.55
77.5	3.89	4.52	2.08
80.0	3.21	3.66	1.30
82.5	2.11	2.28	-0.02
85.0	0.17	-0.04	-2.33
87.5	-4.03	-4.77	-7.10
90.0	-87.00	-86.35	-89.91

Table A-22. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Continued)

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$

$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$

MEDIUM DRY GROUND			
THETA	5 MHz	17.5 MHz	30 MHz
0.0	-84.98	-86.37	-89.90
2.5	-19.47	-26.61	-16.96
5.0	-13.46	-20.51	-10.96
7.5	-9.96	-16.86	-7.47
10.0	-7.48	-14.18	-5.02
12.5	-5.58	-12.02	-3.15
15.0	-4.04	-10.19	-1.65
17.5	-2.76	-8.57	-0.41
20.0	-1.66	-7.12	0.63
22.5	-0.71	-5.79	1.50
25.0	0.12	-4.56	2.24
27.5	0.86	-3.42	2.86
30.0	1.51	-2.36	3.38
32.5	2.09	-1.38	3.79
35.0	2.61	-0.46	4.12
37.5	3.07	0.40	4.36
40.0	3.47	1.19	4.51
42.5	3.83	1.92	4.59
45.0	4.14	2.59	4.60
47.5	4.40	3.20	4.54
50.0	4.62	3.75	4.43
52.5	4.79	4.24	4.29
55.0	4.91	4.66	4.14
57.5	4.99	5.01	3.99
60.0	5.01	5.29	3.88
62.5	4.98	5.50	3.80
65.0	4.88	5.62	3.77
67.5	4.70	5.64	3.75
70.0	4.43	5.54	3.72
72.5	4.04	5.31	3.61
75.0	3.50	4.90	3.37
77.5	2.76	4.26	2.91
80.0	1.70	3.28	2.11
82.5	0.14	1.78	0.76
85.0	-2.38	-0.70	-1.61
87.5	-7.30	-5.61	-6.45
90.0	-84.98	-86.37	-89.90

SAND			
THETA	5 MHz	17.5 MHz	30 MHz
0.0	-84.25	-85.65	-90.27
2.5	-19.22	-28.19	-17.93
5.0	-13.21	-22.04	-11.90
7.5	-9.71	-18.31	-8.38
10.0	-7.24	-15.53	-5.88
12.5	-5.33	-13.24	-3.95
15.0	-3.80	-11.27	-2.39
17.5	-2.51	-9.49	-1.08
20.0	-1.42	-7.88	0.02
22.5	-0.47	-6.39	0.96
25.0	0.36	-5.01	1.77
27.5	1.10	-3.73	2.45
30.0	1.75	-2.54	3.03
32.5	2.32	-1.44	3.50
35.0	2.83	-0.42	3.89
37.5	3.29	0.52	4.18
40.0	3.68	1.37	4.40
42.5	4.03	2.15	4.55
45.0	4.33	2.86	4.63
47.5	4.58	3.49	4.66
50.0	4.78	4.05	4.64
52.5	4.93	4.53	4.59
55.0	5.03	4.94	4.52
57.5	5.08	5.26	4.44
60.0	5.07	5.51	4.35
62.5	5.00	5.67	4.27
65.0	4.86	5.73	4.18
67.5	4.63	5.68	4.06
70.0	4.30	5.50	3.88
72.5	3.84	5.17	3.61
75.0	3.22	4.65	3.17
77.5	2.37	3.88	2.50
80.0	1.19	2.75	1.47
82.5	-0.53	1.06	-0.13
85.0	-3.23	-1.64	-2.76
87.5	-8.38	-6.83	-7.90
90.0	-84.25	-85.65	-90.27

Table A-22. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.5 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Concluded)

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$

THETA	VERY DRY GROUND		
	5 MHz	17.5 MHz	30 MHz
0.0	-85.34	-85.81	-90.28
2.5	-18.98	-36.54	-19.01
5.0	-12.98	-29.95	-12.95
7.5	-9.48	-25.56	-9.37
10.0	-7.01	-22.00	-6.79
12.5	-5.11	-18.90	-4.77
15.0	-3.58	-16.13	-3.10
17.5	-2.30	-13.62	-1.69
20.0	-1.21	-11.34	-0.49
22.5	-0.27	-9.27	0.55
25.0	0.56	-7.39	1.45
27.5	1.28	-5.68	2.21
30.0	1.92	-4.13	2.85
32.5	2.49	-2.72	3.38
35.0	2.99	-1.44	3.81
37.5	3.43	-0.29	4.14
40.0	3.81	0.75	4.39
42.5	4.15	1.69	4.55
45.0	4.43	2.52	4.64
47.5	4.67	3.26	4.67
50.0	4.85	3.90	4.66
52.5	4.99	4.46	4.61
55.0	5.08	4.93	4.54
57.5	5.11	5.31	4.46
60.0	5.08	5.59	4.39
62.5	4.99	5.79	4.31
65.0	4.82	5.87	4.24
67.5	4.56	5.85	4.13
70.0	4.20	5.69	3.97
72.5	3.71	5.37	3.70
75.0	3.05	4.86	3.28
77.5	2.16	4.10	2.61
80.0	0.93	2.97	1.59
82.5	-0.83	1.29	0.00
85.0	-3.59	-1.42	-2.63
87.5	-8.81	-6.60	-7.77
90.0	-85.34	-85.81	-90.28

Table A-23. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$

$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$

THETA	WET GROUND		
	5 MHz	17.5 MHz	30 MHz
0.0	-86.83	-87.34	-89.03
2.5	-20.59	-24.80	-17.30
5.0	-14.58	-18.75	-11.30
7.5	-11.08	-15.17	-7.83
10.0	-8.60	-12.59	-5.39
12.5	-6.69	-10.56	-3.54
15.0	-5.14	-8.87	-2.06
17.5	-3.84	-7.40	-0.86
20.0	-2.73	-6.10	0.14
22.5	-1.76	-4.93	0.96
25.0	-0.90	-3.86	1.64
27.5	-0.15	-2.87	2.20
30.0	0.53	-1.96	2.63
32.5	1.14	-1.11	2.96
35.0	1.69	-0.31	3.19
37.5	2.19	0.43	3.33
40.0	2.63	1.13	3.38
42.5	3.04	1.78	3.36
45.0	3.40	2.38	3.28
47.5	3.72	2.93	3.16
50.0	4.00	3.44	3.03
52.5	4.24	3.89	2.93
55.0	4.45	4.30	2.90
57.5	4.62	4.66	2.97
60.0	4.74	4.95	3.16
62.5	4.83	5.19	3.46
65.0	4.86	5.36	3.82
67.5	4.84	5.45	4.20
70.0	4.76	5.45	4.54
72.5	4.59	5.33	4.78
75.0	4.32	5.08	4.86
77.5	3.89	4.63	4.71
80.0	3.23	3.91	4.24
82.5	2.17	2.72	3.25
85.0	0.29	0.65	1.31
87.5	-3.78	-3.71	-2.99
90.0	-86.83	-87.34	-89.03

THETA	MOIST CLAY		
	5 MHz	17.5 MHz	30 MHz
0.0	-86.94	-86.36	-89.09
2.5	-20.59	-24.11	-16.89
5.0	-14.58	-18.06	-10.90
7.5	-11.07	-14.48	-7.42
10.0	-8.59	-11.92	-4.99
12.5	-6.68	-9.90	-3.14
15.0	-5.13	-8.21	-1.67
17.5	-3.83	-6.76	-0.47
20.0	-2.72	-5.48	0.53
22.5	-1.75	-4.33	1.36
25.0	-0.90	-3.28	2.05
27.5	-0.14	-2.31	2.62
30.0	0.54	-1.42	3.08
32.5	1.15	-0.59	3.44
35.0	1.70	0.18	3.71
37.5	2.20	0.90	3.90
40.0	2.65	1.56	4.01
42.5	3.05	2.18	4.05
45.0	3.41	2.75	4.04
47.5	3.73	3.27	3.99
50.0	4.01	3.75	3.92
52.5	4.26	4.17	3.85
55.0	4.46	4.54	3.79
57.5	4.63	4.85	3.78
60.0	4.76	5.11	3.82
62.5	4.84	5.30	3.90
65.0	4.88	5.41	4.02
67.5	4.86	5.44	4.13
70.0	4.77	5.37	4.20
72.5	4.60	5.18	4.18
75.0	4.32	4.83	4.00
77.5	3.88	4.26	3.59
80.0	3.20	3.38	2.84
82.5	2.09	1.99	1.53
85.0	0.16	-0.35	-0.78
87.5	-4.05	-5.09	-5.55
90.0	-86.94	-86.36	-89.09

Table A-23. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Continued)

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$

$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$

THETA	MEDIUM DRY GROUND		
	5 MHz	17.5 MHz	30 MHz
0.0	-84.89	-86.24	-89.43
2.5	-19.42	-25.22	-17.46
5.0	-13.41	-19.14	-11.47
7.5	-9.91	-15.52	-8.00
10.0	-7.44	-12.88	-5.58
12.5	-5.54	-10.78	-3.74
15.0	-4.00	-9.01	-2.28
17.5	-2.72	-7.46	-1.09
20.0	-1.63	-6.08	-0.11
22.5	-0.68	-4.82	0.71
25.0	0.16	-3.67	1.38
27.5	0.89	-2.61	1.94
30.0	1.54	-1.62	2.40
32.5	2.12	-0.71	2.75
35.0	2.63	0.13	3.03
37.5	3.09	0.91	3.23
40.0	3.49	1.64	3.36
42.5	3.84	2.30	3.45
45.0	4.15	2.91	3.50
47.5	4.41	3.45	3.53
50.0	4.63	3.94	3.56
52.5	4.80	4.37	3.61
55.0	4.92	4.74	3.71
57.5	4.99	5.05	3.84
60.0	5.01	5.28	4.03
62.5	4.98	5.44	4.23
65.0	4.87	5.52	4.44
67.5	4.69	5.50	4.61
70.0	4.42	5.38	4.71
72.5	4.03	5.11	4.69
75.0	3.49	4.68	4.49
77.5	2.74	4.02	4.04
80.0	1.68	3.02	3.23
82.5	0.12	1.50	1.87
85.0	-2.39	-0.99	-0.51
87.5	-7.31	-5.90	-5.36
90.0	-84.89	-86.24	-89.43

THETA	SAND		
	5 MHz	17.5 MHz	30 MHz
0.0	-84.30	-85.52	-89.80
2.5	-19.17	-25.84	-18.03
5.0	-13.16	-19.74	-12.02
7.5	-9.66	-16.10	-8.52
10.0	-7.19	-13.44	-6.06
12.5	-5.29	-11.29	-4.17
15.0	-3.75	-9.47	-2.65
17.5	-2.47	-7.85	-1.40
20.0	-1.38	-6.40	-0.35
22.5	-0.43	-5.07	0.53
25.0	0.40	-3.84	1.27
27.5	1.13	-2.70	1.89
30.0	1.78	-1.64	2.41
32.5	2.35	-0.66	2.83
35.0	2.86	0.25	3.17
37.5	3.31	1.08	3.43
40.0	3.71	1.85	3.63
42.5	4.05	2.54	3.78
45.0	4.34	3.17	3.89
47.5	4.59	3.73	3.98
50.0	4.79	4.22	4.05
52.5	4.94	4.65	4.13
55.0	5.04	5.00	4.22
57.5	5.09	5.27	4.33
60.0	5.07	5.47	4.44
62.5	5.00	5.59	4.54
65.0	4.85	5.61	4.61
67.5	4.62	5.53	4.63
70.0	4.29	5.32	4.56
72.5	3.83	4.96	4.36
75.0	3.21	4.42	3.97
77.5	2.36	3.63	3.33
80.0	1.18	2.48	2.31
82.5	-0.54	0.78	0.72
85.0	-3.24	-1.93	-1.91
87.5	-8.40	-7.13	-7.05
90.0	-84.30	-85.52	-89.80

Table A-23. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 6.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Concluded)

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$

THETA	VERY DRY GROUND		
	5 MHz	17.5 MHz	30 MHz
0.0	-85.30	-85.58	-89.90
2.5	-18.95	-32.45	-19.21
5.0	-12.94	-26.11	-13.17
7.5	-9.44	-22.07	-9.61
10.0	-6.98	-18.92	-7.06
12.5	-5.08	-16.22	-5.08
15.0	-3.55	-13.82	-3.45
17.5	-2.27	-11.65	-2.10
20.0	-1.18	-9.66	-0.94
22.5	-0.24	-7.84	0.04
25.0	0.58	-6.17	0.88
27.5	1.30	-4.64	1.59
30.0	1.94	-3.24	2.19
32.5	2.50	-1.96	2.68
35.0	3.00	-0.80	3.07
37.5	3.44	0.26	3.38
40.0	3.83	1.21	3.62
42.5	4.16	2.06	3.79
45.0	4.44	2.82	3.92
47.5	4.67	3.50	4.02
50.0	4.85	4.08	4.11
52.5	4.99	4.59	4.19
55.0	5.07	5.00	4.28
57.5	5.10	5.34	4.38
60.0	5.07	5.58	4.49
62.5	4.97	5.73	4.59
65.0	4.80	5.79	4.66
67.5	4.55	5.73	4.68
70.0	4.19	5.54	4.61
72.5	3.69	5.20	4.41
75.0	3.03	4.67	4.02
77.5	2.14	3.88	3.38
80.0	0.91	2.74	2.36
82.5	-0.85	1.05	0.77
85.0	-3.61	-1.66	-1.86
87.5	-8.83	-6.86	-7.00
90.0	-85.30	-85.58	-89.90

Table A-24. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 7.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 30, \sigma = 15 \text{ mS/m}$

THETA	WET GROUND		
	5 MHz	17.5 MHz	30 MHz
0.0	-87.01	-87.46	-89.83
2.5	-20.68	-27.43	-16.74
5.0	-14.66	-21.36	-10.72
7.5	-11.16	-17.75	-7.20
10.0	-8.68	-15.13	-4.70
12.5	-6.77	-13.04	-2.78
15.0	-5.21	-11.27	-1.21
17.5	-3.91	-9.72	0.10
20.0	-2.80	-8.33	1.21
22.5	-1.82	-7.04	2.17
25.0	-0.97	-5.85	2.99
27.5	-0.20	-4.74	3.70
30.0	0.48	-3.69	4.30
32.5	1.09	-2.69	4.79
35.0	1.65	-1.75	5.19
37.5	2.15	-0.86	5.50
40.0	2.60	-0.01	5.70
42.5	3.01	0.78	5.80
45.0	3.37	1.53	5.80
47.5	3.70	2.23	5.69
50.0	3.98	2.87	5.48
52.5	4.23	3.46	5.16
55.0	4.44	4.00	4.74
57.5	4.62	4.47	4.23
60.0	4.75	4.89	3.66
62.5	4.84	5.23	3.05
65.0	4.88	5.49	2.48
67.5	4.86	5.67	1.99
70.0	4.78	5.75	1.63
72.5	4.62	5.71	1.38
75.0	4.35	5.52	1.19
77.5	3.92	5.13	0.93
80.0	3.26	4.44	0.44
82.5	2.20	3.29	-0.52
85.0	0.33	1.25	-2.41
87.5	-3.74	-3.10	-6.67
90.0	-87.01	-87.46	-89.83

$\epsilon_r = 10, \sigma = 15 \text{ mS/m}$

THETA	MOIST CLAY		
	5 MHz	17.5 MHz	30 MHz
0.0	-87.08	-86.35	-90.13
2.5	-20.68	-26.68	-17.24
5.0	-14.67	-20.61	-11.22
7.5	-11.16	-17.00	-7.70
10.0	-8.68	-14.38	-5.20
12.5	-6.77	-12.30	-3.27
15.0	-5.21	-10.53	-1.70
17.5	-3.91	-8.99	-0.38
20.0	-2.79	-7.61	0.74
22.5	-1.82	-6.34	1.71
25.0	-0.96	-5.17	2.55
27.5	-0.20	-4.08	3.27
30.0	0.48	-3.05	3.89
32.5	1.10	-2.09	4.41
35.0	1.65	-1.18	4.83
37.5	2.15	-0.31	5.17
40.0	2.61	0.50	5.41
42.5	3.01	1.26	5.57
45.0	3.38	1.97	5.63
47.5	3.71	2.63	5.60
50.0	3.99	3.24	5.48
52.5	4.24	3.79	5.27
55.0	4.45	4.28	4.97
57.5	4.63	4.72	4.61
60.0	4.76	5.08	4.18
62.5	4.85	5.38	3.71
65.0	4.89	5.59	3.23
67.5	4.87	5.71	2.76
70.0	4.79	5.71	2.30
72.5	4.62	5.59	1.84
75.0	4.34	5.30	1.34
77.5	3.91	4.78	0.71
80.0	3.22	3.95	-0.18
82.5	2.12	2.59	-1.56
85.0	0.19	0.28	-3.91
87.5	-4.02	-4.44	-8.69
90.0	-87.08	-86.35	-90.13

Table A-24. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 7.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Continued)

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 10, \sigma = 1.5 \text{ mS/m}$

$\epsilon_r = 4, \sigma = 1.5 \text{ mS/m}$

MEDIUM DRY GROUND			
THETA	5 MHz	17.5 MHz	30 MHz
0.0	-85.09	-86.53	-89.88
2.5	-19.51	-27.99	-17.19
5.0	-13.50	-21.87	-11.18
7.5	-10.00	-18.20	-7.67
10.0	-7.53	-15.49	-5.19
12.5	-5.63	-13.29	-3.28
15.0	-4.09	-11.41	-1.74
17.5	-2.80	-9.74	-0.45
20.0	-1.70	-8.22	0.65
22.5	-0.75	-6.83	1.58
25.0	0.09	-5.53	2.39
27.5	0.83	-4.32	3.09
30.0	1.48	-3.18	3.68
32.5	2.06	-2.12	4.17
35.0	2.58	-1.13	4.58
37.5	3.04	-0.20	4.89
40.0	3.45	0.67	5.11
42.5	3.81	1.47	5.25
45.0	4.12	2.21	5.30
47.5	4.39	2.89	5.26
50.0	4.61	3.51	5.14
52.5	4.78	4.06	4.94
55.0	4.91	4.54	4.69
57.5	4.99	4.95	4.38
60.0	5.01	5.28	4.05
62.5	4.98	5.54	3.73
65.0	4.88	5.70	3.42
67.5	4.71	5.76	3.14
70.0	4.44	5.70	2.88
72.5	4.05	5.50	2.61
75.0	3.52	5.12	2.25
77.5	2.77	4.51	1.72
80.0	1.71	3.55	0.89
82.5	0.15	2.06	-0.48
85.0	-2.36	-0.41	-2.85
87.5	-7.28	-5.31	-7.69
90.0	-85.09	-86.53	-89.88

SAND			
THETA	5 MHz	17.5 MHz	30 MHz
0.0	-84.33	-85.83	-90.14
2.5	-19.26	-31.45	-18.31
5.0	-13.25	-25.19	-12.27
7.5	-9.75	-21.28	-8.73
10.0	-7.28	-18.28	-6.20
12.5	-5.37	-15.75	-4.23
15.0	-3.83	-13.51	-2.63
17.5	-2.55	-11.49	-1.27
20.0	-1.45	-9.64	-0.11
22.5	-0.50	-7.93	0.89
25.0	0.33	-6.35	1.76
27.5	1.07	-4.89	2.51
30.0	1.72	-3.54	3.16
32.5	2.30	-2.30	3.70
35.0	2.81	-1.16	4.16
37.5	3.27	-0.11	4.52
40.0	3.67	0.85	4.79
42.5	4.02	1.72	4.99
45.0	4.32	2.51	5.10
47.5	4.57	3.21	5.13
50.0	4.77	3.84	5.10
52.5	4.93	4.39	5.00
55.0	5.03	4.85	4.86
57.5	5.08	5.23	4.67
60.0	5.08	5.53	4.45
62.5	5.01	5.73	4.21
65.0	4.87	5.83	3.96
67.5	4.64	5.82	3.69
70.0	4.31	5.68	3.38
72.5	3.86	5.38	2.99
75.0	3.23	4.89	2.48
77.5	2.39	4.14	1.75
80.0	1.21	3.03	0.69
82.5	-0.51	1.36	-0.93
85.0	-3.21	-1.34	-3.57
87.5	-8.36	-6.52	-8.72
90.0	-84.33	-85.83	-90.14

Table A-24. Antenna Directivity in dBi versus Polar Angle Theta (θ) for Three Frequencies and Five Soil Conditions, for 7.0 Meter High Monopole with 12 Meter Radius Ground Screen of 16 Radials (Concluded)

(Elevation Angle $\psi = 90^\circ - \theta$)

$\epsilon_r = 4, \sigma = 0.15 \text{ mS/m}$

THETA	VERY DRY GROUND		
	5 MHz	17.5 MHz	30 MHz
0.0	-85.40	-86.10	-90.12
2.5	-19.02	-37.48	-19.35
5.0	-13.01	-31.14	-13.28
7.5	-9.51	-27.05	-9.67
10.0	-7.04	-23.71	-7.06
12.5	-5.15	-20.69	-5.00
15.0	-3.61	-17.89	-3.28
17.5	-2.33	-15.27	-1.82
20.0	-1.24	-12.85	-0.56
22.5	-0.30	-10.62	0.54
25.0	0.53	-8.58	1.50
27.5	1.26	-6.72	2.33
30.0	1.90	-5.04	3.03
32.5	2.47	-3.51	3.63
35.0	2.97	-2.12	4.12
37.5	3.41	-0.87	4.51
40.0	3.80	0.26	4.80
42.5	4.14	1.27	5.00
45.0	4.43	2.18	5.11
47.5	4.66	2.99	5.14
50.0	4.85	3.70	5.10
52.5	4.99	4.31	5.00
55.0	5.08	4.83	4.84
57.5	5.11	5.26	4.65
60.0	5.09	5.59	4.44
62.5	5.00	5.82	4.21
65.0	4.83	5.95	3.98
67.5	4.58	5.96	3.73
70.0	4.22	5.83	3.44
72.5	3.73	5.54	3.08
75.0	3.07	5.06	2.59
77.5	2.18	4.31	1.88
80.0	0.96	3.20	0.83
82.5	-0.81	1.53	-0.77
85.0	-3.57	-1.16	-3.41
87.5	-8.79	-6.34	-8.55
90.0	-85.40	-86.10	-90.12